31L48TPBM240

TIME RELAY ON DELAY. MULTISCALE AND SINGLE VOLTAGE, PLUG-IN AND FLUSH-MOUNT VERSION 48X48MM, 220...240VAC



Product designation			Time relay
Product type designation			L48TPB
General characteristics			
Description			On delay time relay, multiscale and multivoltage, plug-in version
Function			On delay
Supply circuit			
Rated auxiliary supply voltage Us			220…240VAC
Rated auxiliary supply voltage Us			
AC			
	min	VAC	220
	Max	VAC	240
Rated frequency		Hz	50/60
Operating voltage range			0.85...1.1 Us
Maximum power consumption / dissipation		W	6VA
Immunity time for microbreakings		ms	≤40
Timing circuit			
Time setting range			0.05s…10min
Setting accuracy		%	±5
Repeat accuracy		%	±0.5
Influence of voltage variation		%	±0.5
Resetting time			
	During timing	ms	≥100
	Elapsed time	ms	≥65
Relay outputs			
Number of relays		Nr.	2
Contact arrangement			2 delayed C/O or 1 instananeous C/O + 1 delayed C/O
Maximum switching voltage		VAC	250
IEC Conventional free air thermal current Ith		A	5
UL/CSA and IEC/EN 60947-5-1 designation			B300
Insulation (input-output)			
Rated insulation voltage Ui		V	250
Power frequency withstand voltage		kV	2
Operations			
Mechanical life		cycles	30000000
Electrical life (with rated load)		cycles	100000
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-10
	max	°C	+60


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Storage temperature			
	min	°C	-30
	max	°C	+80


Housing

Material			Self-extinguishing polyamide
Mounting			Plug-in housing with 8-pin socket
Degree of protection			IP40 on front, IP20 terminals
Dimensions (W x H x D)		mm	48 x 48 x 90
Weight		g	124

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n°14	
IEC/EN 61812-1	
UL508	

Certificates

cURus	
EAC	

ETIM classification

ETIM 8.0	EC001439 - Timer relay

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding