LVM40A127

LEVEL MONITORING RELAY, MODULAR VERSION, SINGLE-VOLTAGE. MULTIFUNCTIONS. AUTOMATIC RESETTING, 110...127VAC



Product designation			Level control relay multifunction. Single voltage. Modular version
Product type designation			LVM40
Function			Multifunction: emptying and alarms, filling and alarms, emptying with priority start-up change, filling with priority start-up change, well draining and tank filling and alarms
Auxiliary supply			
Supply voltage Type			Single voltage
Rated auxiliary supply voltage Us AC			
	min	VAC	110
	Max	VAC	127
Operating voltage range			0.85...1.1 Us
Rated frequency		Hz	50/60
Power consumption Max		VA	4.5
Power dissipation Max		W	2.8
Output characteristics			
Number of connectable electrodes		Nr.	5
Type of electrode			Electrode and electrode holders: SN1 / SCM / CGL / PS31 / PS3S or similar
Electrode voltage			10 Vpp
Sensitivity		kΩ	2.5...200 adjustable
Time delay			
Tripping time		s	1
Resetting time		s	1
Probe tripping delay			1…10s
Relay outputs			
Number of relays		Nr.	2
Relay state			Normally de-energised, energises at tripping

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Contact arrangement			1 changeover contact C/O-SPDT + 1 contact NO-SPST
Rated operational voltage AC (IEC)		VAC	250
Maximum switching voltage		VAC	400
IEC Conventional free air thermal current Ith		A	8
UL/CSA and IEC/EN 60947-5-1 designation			B300
Electrical life (with rated load)		cycles	10^5
Mechanical life		cycles	$30x10^6$
Indications			
Indication			1 green LED indicator for power on 2 red LEDs for relay state 2 red LEDs for probe state
Functions			
3 detecting electrodes (MIN, MAX and COM)			No
5 detecting electrodes (MIN1, MAX1, MIN2, MAX2 and COM			Yes
Sensitivity adjustment 2.5...50k Ω			No
Sensitivity adjustment 2.5...100k Ω			No
Sensitivity adjustment 2.5...200k Ω			Yes
Adjustable sensitivity full-scale value 25-50-100-200 k Ω			Yes
Separate sensitivity adjustment for MAX probe (foam detection)			Yes
Emptying function			Yes
Filling function			Yes
Emptying function with MIN and/or MAX alarm			Yes
Filling function with MIN and/or MAX alarm			Yes
Emptying function with pump priority change			Yes
Filling function with pump priority change			Yes
Tank filling, well drawing and alarm			Yes
Filling-emptying adjustment selector			No
Programming selector for 5 different			Yes
Motor start-up priority change			No
Connections			
Tightening torque for terminals			
	max	Nm	0.8
	max	lbin	7
Conductor cross section			
AWG/Kcmil			
	min	AWG	24
	Max	AWG	12
IEC			
	min	mm^2	0.2
	Max	mm^2	4
Insulations			
Rated insulation voltage Ui		V	415
Rated impulse withstand voltage Uimp		kV	6
Operating frequency withstand voltage		kV	4
Double insulation Supply / relay / electrode		VAC	≤250
Ambient conditions			
Temperature			


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Operating temperature			
	min	°C	-20
	max	°C	+60
Storage temperature			
	min	°C	-30
	max	°C	+80

Housing

Execution		Modular DIN rail mounting
N° of modules		3
Material		Self-extinguishing polyamide
Mounting		35mm DIN rail (IEC/EN 60715) or by screws using extractable clips
IEC degree of protection		IP40 on front / IP20 on terminals
Dimensions (W x H x D)	mm	53.5 x 104.7 x 64.9
Weight	g	278

Dimensions




Wiring diagrams

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

LVM40A127

LEVEL MONITORING RELAY, MODULAR VERSION, SINGLE-VOLTAGE. MULTIFUNCTIONS. AUTOMATIC RESETTING, 110...127VAC



Certifications and compliance

Compliance

CSA C22.2 n° 14
IEC/EN 60255-5
IEC/EN 61000-6-2
IEC/EN 61000-6-3
UL508

Certificates

cULus
EAC

ETIM classification

ETIM 8.0	EC001447 - (Fill) level monitoring relay

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding