SMR 3012 AP 5

Thru Beam

Photoelectric Sensors

Compatible Transmitter:
SMT 3012C AP 5



Product Data	
Function	Receiver
Operation Mode	Thru Beam
Supply Voltage	10 - 30 V dc
Connection	5 m cable
Sensing Range	12 m
Output	NPN
Output Status	N.C.
Housing Material	Plastic
Housing	Ø10


Technical Data	
Supply Voltage	10 - 30 V dc
Voltage Ripple	15 %
Reverse Polarity Protected	Yes
Short Circuit Protected	Yes
Current Consumption	Max. 8 mA
Max. Output Load	100 mA
Max. Residual Voltage	2,5 V
Max. Operation Frequency	> 90 Hz
Response Time ton / toff	< 4 ms / < 6 ms
Output Indicator	Yellow LED
Hysteresis	Approx. 25 %
Opening Angle	+/- 3°
Housing Material, Front Lens	Polycarbonate
Housing Material, Sensor Housing	Polycarbonate
Cable	3 x 0,14 mm²
Cable Sleeve	PVC Ø 3,4 mm

COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.


Environmental Data	
Vibration	10 - 55 Hz, 0,5 mm
Shock	30 g
Operation Temperature	-20 to +50 °C
Storage Temperature	-40 to +80 °C
Sealing Class	IP 67
Light Immunity 5˚	12 000 lux

Approvals

Wiring Diagram




Parallel Displacement




SMT 3012 and SMR 3x12

COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Angular Displacement



Dimensions



COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.