

EF303.2

- **Screw connection**
- **Mounting flange position 2**
- **Suitable for EMERGENCY-OFF**
- **31-32; 43-44 (Contact labelling)**

Data

Ordering data	
	EF 303.2
	101022138
EAN (European Article Number)	4250116201358
eCl@ss number, Version 9.0	27-37-13-02
Approval - Standards	
	cULus CCC EAC
General data	
Product name	Contact element EF
	EN 60947-5-1 IEC/EN 60947-1
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Contact labelling	43-44
Gross weight	35 g
General data - Features	
Suitable for EMERGENCY-OFF	Yes
Number of openers	1
Number of shutters	1

Mechanical data	
Installation instructions	pluggable
Mechanical life, minimum	10,000,000 Operations
positive break travel	2 mm
Contact opening	3 mm
Note Bounce duration	Bounce duration at an Actuating speed of 100mm/s
	2
Mechanical data - Connection technique	
Terminal Connector	Screw connection
Cable section, minimum	0.5 mm², rigid 0.5 mm², flexible
Cable section, maximum	2.5 mm², rigid 1.5 mm², flexible
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Mechanical data - Dimensions	
Width	10 mm
Length	46 mm
Depth	60 mm
Ambient conditions	
	IP40
	IP20
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+80 °C
	110 g / 4 ms
Resistant to vibration	Resistance to vibration: 20 g / 10…200 Hz
Electrical data	
Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	8 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	5 A
	≥ 5 V / ≥ 3.2 mA
Switching element	NC contact, NO contact
Switching principle	Slow action
Bounce duration, maximum	5 ms

Switching frequency	1,200 /h

Pictures


Photo/Product/Catalogue



ID: ef303f02

| 50,5 kB | .png | 74.083 x 74.083 mm - 210 x 210 Pixel - 72 dpi
| 617,8 kB | .jpg | 352.778 x 352.778 mm - 1000 x 1000 Pixel - 72 dpi


Diagramm/Product/Travel



ID: krf--s10

| 1,2 kB | .png | 74.083 x 31.044 mm - 210 x 88 Pixel - 72 dpi
| 19,0 kB | .cdr |
| 31,8 kB | .jpg | 352.778 x 147.814 mm - 1000 x 419 Pixel - 72 dpi

Illistration/Product/Function



ID: krf--a05

| 189,7 kB | .jpg | 352.778 x 711.2 mm - 1000 x 2016 Pixel - 72 dpi
| 19,5 kB | .cdr |
| 3,7 kB | .png | 74.083 x 149.225 mm - 210 x 423 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on 572021-01-31T14:27:57+01:000201Europe/BerlinSun, 31 Jan 2021 14:27:57 +010057pmSunday.31pm31Europe/BerlinCET2701Europe/BerlinJanuary2021Sun, 31 Jan 2021 14:27:57 +010001pm31