

UVH 434Y

- **4 Contacts**
- **Metal enclosure**
- **3 cable entries M 20 x 1.5**
- **Lever can be transposed by 180°**
- **62 mm x 127 mm x 50 mm (basic component)**
- **Continuous adjustment of lever position 360°**
- **Switching points and contact function adjustable**
- **Actuator head can be repositioned in steps 4 x 90°**

Data

Ordering data	
	UVH 434Y
	101175233
EAN (European Article Number)	4030661304526
eCl@ss number, Version 9.0	27-27-06-01
Approval - Standards	
	EAC
General data	
Product name	U 434 roller lever H
	EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Light alloy die-casting
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	550 g
General data - Features	
Number of openers	2
Number of shutters	2

Safety appraisal - Safety outputs	
B10d Normally-closed contact (NC)	2,000,000 Operations
Mechanical data	
Actuating element	Roller lever
Mechanical life, minimum	10,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	2 x 1.5 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	3 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis
Mechanical data - Connection technique	
Terminal Connector	Screw connection
	1.5 mm²
	2.5 mm²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG
Mechanical data - Dimensions	
Height of sensor	185 mm
Length of sensor	50 mm
Width of sensor	62 mm
Width of Castor	8.5 mm
Diameter of Castor	20 mm
Ambient conditions	
Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-20 °C
Ambient temperature, maximum	+60 °C
Electrical data	
Thermal test current	16 A
Switching element	NC contact NO contact
Switching principle	Creep circuit element
Notes	
Note (General)	Type of contact and switching points can be factory set to order.

Ordering code

Product type description:

U(1) 434Y-(2)-(3)

(1)

S Plunger S
K Offset roller lever K
8H Roller lever 8H
H Roller lever H
3H Roller lever 3H
7H Roller lever 7H
4H Spring rod lever on shaft 4H
9H Rod lever 9H
10H Rod lever 10H
2H Leaf spring lever 2H
6H Leaf spring lever 6H

(2)

without 2 NO contacts/2 NC contact
4OE 4 NC contact
4S 4 NO contacts
1S/3OE 1 NO contacts/3 NC contact
3S/1OE 3 NO contacts/1 NC contact

(3)

1272 Version for low temperatures to -30 °C

Pictures

Photo/Product/Catalogue



ID: ku43sf04

| 65,9 kB | .png | 74.083 x 120.297 mm - 210 x 341 Pixel - 72 dpi
| 978,8 kB | .jpg | 352.425 x 573.617 mm - 999 x 1626 Pixel - 72 dpi


Photo/Product/Catalogue



ID: ku43hf29

| 603,4 kB | .jpg | 178.858 x 370.417 mm - 507 x 1050 Pixel - 72 dpi
| 110,2 kB | .png | 74.083 x 153.106 mm - 210 x 434 Pixel - 72 dpi

Dimension/Product/Basic



ID: 1u43-g04

| 4,2 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel - 72 dpi
| 91,2 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703 Pixel - 72 dpi
| 27,6 kB | .cdr |


Diagramm/Product/Travel



ID: ku43-s03

| 93,9 kB | .jpg | 352.778 x 182.386 mm - 1000 x 517 Pixel - 72 dpi
| 1,2 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel - 72 dpi


Graphic/Product/Contact



ID: k2o2sk04

| 19,1 kB | .cdr |
| 81,1 kB | .jpg | 352.778 x 379.236 mm - 1000 x 1075 Pixel - 72 dpi

Illistration/Product/Function




ID: ku432a01

| 19,8 kB | .png | 74.083 x 49.742 mm - 210 x 141 Pixel - 72 dpi
| 203,1 kB | .cdr |
| 157,4 kB | .jpg | 352.778 x 236.361 mm - 1000 x 670 Pixel - 72 dpi

Illistration/Product/Function






ID: 235hz05

| 15,2 kB | .cdr |
| 180,5 kB | .jpg | 352.778 x 749.3 mm - 1000 x 2124 Pixel - 72 dpi
| 3,4 kB | .png | 74.083 x 157.339 mm - 210 x 446 Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1t15vb01

| 10,3 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel - 72 dpi
| 114,5 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on 172021-01-31T15:41:17+01:000301Europe/BerlinSun, 31 Jan 2021 15:41:17 +010017pmSunday.31pm31Europe/BerlinCET4101Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:41:17 +010001pm31