LVMP30A240

START-UP PRIORITY CHANGE RELAY FOR 3 OR 4 MOTORS, MODULAR VERSION.
AUXILIARY SUPPLY VOLTAGE 100…240VAC



Product designation			Start-up priority change relay. Modular version
Product type designation			LVMP30
Function			Priority change for 3-4 motors
Auxiliary supply			
Supply voltage Type			Multi voltage
Rated auxiliary supply voltage Us			
AC			
	min	VAC	85
	Max	VAC	265
Operating voltage range			85…265VAC
Rated frequency		Hz	50/60
Operational frequency			
	min	Hz	47
	max	Hz	63
Power dissipation Max		W	7.5
Relay outputs			
Number of relays		Nr.	4
Relay state			Normally de-energised, energises at tripping
Contact arrangement			4 NO
Rated operational voltage AC (IEC)		VAC	250
Maximum switching voltage		VAC	265
IEC Conventional free air thermal current Ith		A	8
Electrical life (with rated load)		cycles	10^5
Indications			
Indication			Display for monitoring motor status, number of starts and working hours
Functions			
3 detecting electrodes (MIN, MAX and COM)			No
5 detecting electrodes (MIN1, MAX1, MIN2, MAX2 and COM			No
Sensitivity adjustment 2.5...50k Ω			No
Sensitivity adjustment 2.5...100k Ω			No
Sensitivity adjustment 2.5...200k Ω			No
Adjustable sensitivity full-scale value 25-50-100-200 k Ω			No
Separate sensitivity adjustment for MAX probe (foam detection)			No
Emptying function			No
Filling function			No
Emptying function with MIN and/or MAX alarm			No


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Filling function with MIN and/or MAX alarm				No
Emptying function with pump priority change				No
Filling function with pump priority change				No
Tank filling, well drawing and alarm				No
Filling-emptying adjustment selector				No
Programming selector for 5 different				No
Motor start-up priority change				Yes
Connections				
Terminals type				Screw
Tightening torque for terminals				
		max	Nm	0.6
		max	Ibin	5.3
Conductor cross section				
	AWG/Kcmil			
		min	AWG	26
		Max	AWG	14
	IEC			
		min	mm²	0.14
		Max	mm²	2.5
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-20
		max	°C	+55
	Storage temperature			
		min	°C	-40
		max	°C	+70
Relative humidity			%	20…90
Housing				
Execution				Modular DIN rail mounting
N° of modules				4
Material				Polyamide
Mounting				35mm DIN rail (IEC/EN 60715) or by screws using extractable clips
IEC degree of protection				IP20
Dimensions (W x H x D)			mm	72 x 106 x 59.6
Weight			g	242
Dimensions				


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

LVMP30A240

START-UP PRIORITY CHANGE RELAY FOR 3 OR 4 MOTORS, MODULAR VERSION.
AUXILIARY SUPPLY VOLTAGE 100…240VAC



Wiring diagrams



Terminals / Morsetti	Description	Descrizione
L-N	Auxiliary supply: LVMP30A024: 24VAC 50/60Hz LVMP30A240: 100…240VAC 50/60Hz	Alimentazione ausiliaria: LVMP30A024: 24VAC 50/60Hz LVMP30A240: 100…240VAC 50/60Hz
I1	Minimum level (enable)	Livello minimo (abilitazione)
I2	Start pump 1 input	Ingresso start pompa 1
I3	Start pump 2 input	Ingresso start pompa 2
I4	Start pump 3 input	Ingresso start pompa 3
I5	Start pump 4 input	Ingresso start pompa 4
I6	Latch enable	Abilitazione memoria
Q1	Pump 1 command output	Uscita comando pompa 1
Q2	Pump 2 command output	Uscita comando pompa 2
Q3	Pump 3 command output	Uscita comando pompa 3
Q4	Pump 4 command output	Uscita comando pompa 4

Certifications and compliance

Compliance

	CSA C22.2 n°142
	IEC/EN/BS 61131-2
	UL508

Certificates

	cULus
	EAC

ETIM classification

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

ETIM 8.0	EC001447 - (Fill) level monitoring relay

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding