

PZ-M62

Square retro-reflective M8 Connector Type, NPN

*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

Specifications


Model		PZ-M62
Type		Retro-reflective model (with P.R.O function; M8 connector cable type)
Output		NPN
Detecting distance		0.1 to 1.5 m*1 (when reflector R-5 is used)*2
Setting distance		—
Light source.		Red LED
Sensitivity adjustment		1-turn trimmer (230°)
Response time		1 ms max.
Operation mode		LIGHT-ON/DARK-ON (switch-selectable)
Indicator lamp		Output: orange LED, stable operation: green LED
Control output		100 mA (40 V) max.Residual voltage: 1 V max.
Digital monitor		—
Protection circuit		Reversed polarity, overcurrent protection, surge absorber
Rating	Power voltage	12 to 24 VDC ±10 %, Ripple (P-P) 10 % or less
	Power consumption	34 mA max.
Environmental resistance	Enclosure rating	IP67
	Ambient light	Incandescent lamp: 5,000 lux max., Sunlight: 20,000 lux max.
	Ambient temperature	-20 to +55 °C -4 to 131 °F (No freezing)
	Relative humidity	35 to 85 % RH (No condensation)
	Vibration resistance	10 to 55 Hz, Double amplitude 1.5 mm 0.06", 2 hours in each of the X, Y, and Z directions
	Shock resistance	1,000 m/s², 6 times in each of the X, Y, and Z directions
Case material		Glass-fiber reinforced plastic
Weight		Approx. 15 g

*1 1 reflector R-5 is included with the PZ-M61.
*2 The detecting distance is obtained with the maximum sensitivity.


Dimensions

* Download CAD file or product manual for larger image/text and more detail.

pz_m62_dimension_01.gif



pz_m62_dimension_02.gif



ピン番号	
1	12–24V DC
2	L.ON/D.ON切換
3	0V
4	出力

pz_m62_dimension_031229568794427.gif

