TL 441-11Y



- 2 Contacts
- Metal enclosure
- Protection class IP65
- 2 cable entries M 20 x 1.5
- Lever can be transposed by 180°
- 106 mm x 99 mm x 63 mm (basic component)
- Continuous adjustment of lever position 360°
- Actuator head can be repositioned in steps 4 x 90°
- In temperature-resistant version, the roller can be mounted in two different positions on the shaft

Data

Ordering data	
	TL 441-11Y
	101059310
EAN (European Article Number)	4030661035482
eCl@ss number, Version 9.0	27-27-06-01
Approval - Standards	
	DNV.GL CCC EAC
General data	
Product name	441 roller lever L
	EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Grey cast iron, galvanised
Enclosure coating material	painted
Material of the contacts, electrical	Silver

Roller material	Plastic
Gross weight	1,605 g
General data - Features	
Number of openers	1
Number of shutters	1
Safety appraisal - Safety outputs	
B10d Normally-closed contact (NC)	2,000,000 Operations
Mechanical data	
Actuating element	Roller lever
Mechanical life, minimum	10,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	2 x 6 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	3 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis
Mechanical data - Connection technique	
Terminal Connector	Screw connection
	1.5 mm²
	2.5 mm²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG
Mechanical data - Dimensions	
Height of sensor	192 mm
Length of sensor	63 mm
Width of sensor	106 mm
Width of Castor	9 mm
Diameter of Castor	36 mm
Ambient conditions	
Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C
Ambient conditions - Insulation value	
Rated impulse withstand voltage	6 kV

Electrical data

Thermal test current	16 A
Utilisation category AC-15	400 VAC
Utilisation category AC-15	4 A
Switching element	NO contact, NC contact
Note (Switching element)	with double break
Switching principle	Creep circuit element

Ordering code

Product type description:

(1)(2) 441-11Y(3)-(4)-(5)

(1)

T Slow action (not available for AF/S)

M Snap action

(2)

S Plunger S

2S Telescopic plunger 2S

R Roller plunger R

K Offset roller lever K

J Offset roller lever J

2C Fork lever 2C

L Roller lever L

D Roller lever D

MAF/S Level switch AF/S

(3)

UE Slow action with overlapping contacts

(4)

without Cast iron enclosure

A Aluminium enclosure

(5)

T temperature-resistant and tropical version with ceramic insulation for -40 °C ... +200 °C

1276-2 Gold-plated contacts

Pictures


Photo/Product/Catalogue



ID: kt441f08

| 77,2 kB | .png | 74.083 x 118.181 mm - 210 x 335 Pixel - 72 dpi
| 530,6 kB | .jpg | 215.547 x 344.664 mm - 611 x 977 Pixel - 72 dpi

Dimension/Product/Basic



ID: 1t441g01

| 3,9 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel - 72 dpi
| 29,6 kB | .cdr |
| 86,4 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701 Pixel - 72 dpi


Diagramm/Product/Travel



ID: kt441s06

| 1,0 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel - 72 dpi
| 55,1 kB | .jpg | 352.778 x 159.456 mm - 1000 x 452 Pixel - 72 dpi


Dimension/Product/Actuator



ID: 1t422b07

| 113,5 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695 Pixel - 72 dpi
| 9,8 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel - 72 dpi

Illistration/Product/Function



ID: 235hz05

| 15,2 kB | .cdr |
| 180,5 kB | .jpg | 352.778 x 749.3 mm - 1000 x 2124 Pixel - 72 dpi
| 3,4 kB | .png | 74.083 x 157.339 mm - 210 x 446 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on 102021-01-31T15:48:10+01:000301Europe/BerlinSun, 31 Jan 2021 15:48:10 +010010pmSunday.31pm31Europe/BerlinCET4801Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:48:10 +010001pm31