

UV3H 432Y

- **2 Contacts**
- **Metal enclosure**
- **3 cable entries M 20 x 1.5**
- **Lever can be transposed by 180°**
- **62 mm x 80 mm x 50 mm (basic component)**
- **Continuous adjustment of lever position 360°**
- **Switching points and contact function adjustable**
- **Actuator head can be repositioned in steps 4 x 90°**

Data

Ordering data	
	UV3H 432Y
	101060537
EAN (European Article Number)	4030661046686
eCl@ss number, Version 9.0	27-27-06-01
Approval - Standards	
	EAC
General data	
Product name	U 432 roller lever 3H
	EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Light alloy die-casting
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	470 g
General data - Features	
Number of openers	2

Safety appraisal - Safety outputs	
B10d Normally-closed contact (NC)	2,000,000 Operations
Mechanical data	
Actuating element	Roller lever
Mechanical life, minimum	10,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	2 x 1.5 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	3 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis
Mechanical data - Connection technique	
Terminal Connector	Screw connection
	1.5 mm²
	2.5 mm²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG
Mechanical data - Dimensions	
Height of sensor	176 mm
Length of sensor	50 mm
Width of sensor	62 mm
Width of Castor	8 mm
Diameter of Castor	36 mm
Ambient conditions	
Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-20 °C
Ambient temperature, maximum	+60 °C
Electrical data	
Thermal test current	16 A
Switching element	Opener (NC)
Switching principle	Creep circuit element
Notes	
Note (General)	Type of contact and switching points can be factory set to order.

Ordering code

Product type description:

U(1) 432Y-(2)-(3)

(1)

S Plunger S
K Offset roller lever K
8H Roller lever 8H
H Roller lever H
3H Roller lever 3H
7H Roller lever 7H
4H Spring rod lever on shaft 4H
9H Rod lever 9H
10H Rod lever 10H
2H Leaf spring lever 2H
6H Leaf spring lever 6H

(2)

without 2 NC contact
2S 2 NO contacts
1S/1OE 1 NO contacts/1 NC contact

(3)

1272 Version for low temperatures to -30 °C

Pictures


Photo/Product/Catalogue



ID: ku43hf03

| 483,9 kB | .jpg | 155.575 x 345.369 mm - 441 x 979 Pixel - 72 dpi
| 130,0 kB | .png | 74.083 x 164.394 mm - 210 x 466 Pixel - 72 dpi

Dimension/Product/Basic



ID: 1u43-g02

| 82,9 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701 Pixel - 72 dpi
| 3,7 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel - 72 dpi
| 27,7 kB | .cdr |


Diagramm/Product/Travel



ID: ku43-s03

| 93,9 kB | .jpg | 352.778 x 182.386 mm - 1000 x 517 Pixel - 72 dpi
| 1,2 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel - 72 dpi


Graphic/Product/Contact



ID: k2o1sk02

| 18,4 kB | .cdr |
| 82,3 kB | .jpg | 352.778 x 193.322 mm - 1000 x 548 Pixel - 72 dpi


Illistration/Product/Function



ID: ku432a01

| 19,8 kB | .png | 74.083 x 49.742 mm - 210 x 141 Pixel - 72 dpi
| 203,1 kB | .cdr |
| 157,4 kB | .jpg | 352.778 x 236.361 mm - 1000 x 670 Pixel - 72 dpi


Illistration/Product/Function



ID: 235hz05

| 15,2 kB | .cdr |
| 180,5 kB | .jpg | 352.778 x 749.3 mm - 1000 x 2124 Pixel - 72 dpi
| 3,4 kB | .png | 74.083 x 157.339 mm - 210 x 446 Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1t15vb04

| 9,3 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel - 72 dpi
| 93,3 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on 012021-01-31T15:32:01+01:000301Europe/BerlinSun, 31 Jan 2021 15:32:01 +010001pmSunday.31pm31Europe/BerlinCET3201Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:32:01 +010001pm31