

T1K335-03Z-M20

- **Metal enclosure**
- **Design to EN 50041**
- **40,5 mm x 76 mm x 38 mm**
- **1 Cable entry M 20 x 1.5**
- **Wide range of alternative actuators**
- **Good resistance to oil and petroleum spirit**
- **Actuator heads can be repositioned by 4 x 90°**

Data

Ordering data	
	T1K 335-03Z
	101147379
EAN (European Article Number)	4030661142876
eCl@ss number, Version 9.0	27-27-26-01
Approval - Standards	
	cULus CCC EAC
General data	
Product name	T 335 offset roller lever 1K
Housing construction form	Norm construction design
Enclosure material	Aluminium
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Gross weight	205 g
General data - Features	
Safety functions	Yes
Number of safety contacts	3
Safety appraisal	

	BG-GS-ET-15 ISO 13849-1 EN 60947-5-1
Mission Time	20 Year(s)
Safety appraisal - Safety outputs	
B10d Normally-closed contact (NC)	20,000,000 Operations
Mechanical data	
Actuating element	Offset roller lever
Mechanical life, minimum	30,000,000 Operations
Actuating force, minimum	17 N
Actuating speed, maximum	0.5 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note (Switchover time)	Switchover time in accordance with actuating speed
Mechanical data - Connection technique	
Terminal Connector	Screw connection
	0.75 mm²
	2.5 mm²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Mechanical data - Dimensions	
Height of sensor	118.5 mm
Length of sensor	38 mm
Width of sensor	40.5 mm
Ambient conditions	
	IP67
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C
Ambient conditions - Insulation value	
Rated impulse withstand voltage	4 kV
Electrical data	
Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A

Utilisation category DC-13	24 VDC
Utilisation category DC-13	4 A
Switching element	Opener (NC)
Switching principle	Slow action
Bounce duration, maximum	2 ms
Switching frequency	5,000 /h

Ordering code

Product type description:

(1)(2) 3(3)5-(4)Z(5)-(6)-(7)-(8)-(9)

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

H Roller lever H

10H Rod lever 10H

7H Roller lever 7H

1K Offset roller lever 1K

3K Angle roller lever 3K

RMS Brass roller

(3)

3 slim design

5 large design

(4)

11 1 NO contacts/1 NC contact

02 2 NC contact

20 2 NO contacts (not suitable for safety applications)

01/01 1 NC contact left / 1 NC contact right

12 1 NO contact/2 NC contacts

03 3 NC contact

(5)

H Slow action with staggered contacts

UE Slow action with overlapping contacts

(6)

G24 with LED

(7)

without	Cable entry M20
NPT	Cable entry NPT 1/2"
ST	M12 connector with A-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)
ST-2310	M12 connector with B-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)

(8)

2138 Roller lever 7H for position switches with safety function


(9)

1637 Gold-plated contacts

Pictures

Photo/Product/Catalogue	
	ID: k335kf01 | 124,4 kB | .png | 74.083 x 164.747 mm - 210 x 467 Pixel - 72 dpi | 486,9 kB | .jpg | 159.103 x 354.542 mm - 451 x 1005 Pixel - 72 dpi
Photo/Product/Catalogue	
	ID: k335sf01 | 156,7 kB | .png | 74.083 x 166.511 mm - 210 x 472 Pixel - 72 dpi | 454,9 kB | .jpg | 136.172 x 306.211 mm - 386 x 868 Pixel - 72 dpi


Dimension/Product/Basic



ID: 1-335g01

| 105,8 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697 Pixel - 72 dpi
| 4,5 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel - 72 dpi
| 96,7 kB | .cdr |


Diagramm/Product/Travel



ID: kk335s25

| 24,8 kB | .cdr |
| 1,8 kB | .png | 74.083 x 25.047 mm - 210 x 71 Pixel - 72 dpi
| 51,9 kB | .jpg | 352.778 x 119.239 mm - 1000 x 338 Pixel - 72 dpi


Graphic/Product/Contact



ID: k3o3sk01

| 82,7 kB | .jpg | 352.778 x 191.558 mm - 1000 x 543 Pixel - 72 dpi
| 18,9 kB | .cdr |
| 2,4 kB | .png | 74.083 x 40.217 mm - 210 x 114 Pixel - 72 dpi
| 6,7 kB | .png | 50.038 x 27.178 mm - 591 x 321 Pixel - 300 dpi
| 2,4 kB | .jpg | 33.161 x 17.992 mm - 94 x 51 Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1k336g01

| 71,4 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697 Pixel - 72 dpi
| 7,0 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel - 72 dpi
| 57,2 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on 072021-01-31T04:31:07+01:000401Europe/BerlinSun, 31 Jan 2021 04:31:07 +010007amSunday.31am31Europe/BerlinCET3101Europe/BerlinJanuary2021Sun, 31 Jan 2021 04:31:07 +010001am31