MC36C

Compact safety magnetic sensors



Description

The MC36C series are encoded safety magnetic sensors with compact housing used to monitor the position of hinged, sliding or removable guards of industrial applications.
Carlo Gavazzi safety sensors stop or disconnect the dangerous motions, if the mobile protections are opened or displaced. They are suitable for safety gates applications up to safety category 4, PLe according to EN ISO 13849-1 with suitable logic safety module.
MC36C sensors are the right answer in harsh industrial environments with damp and dusty condition.

Benefits

- **Standards compliance.** Up to Cat. 4 PL e in accordance with EN ISO 13849-1.
- **Customizable.** The sensors are available with left or right exit, integrated cable, M8 or pigtail with M12 connector and optionally LED indicator.
- **High performance.** Reinforced polymeric casing (PBT) with a protection degree IP67, operating temperature range from -25°C to +80°C. IP69K for M8 versions without LED.
- **Compact dimensions.** Only 36 x 26 x 13 mm
- **Different outputs.** 2NO, 1NO + 1NC or 2NO + 1NC. (The status of the output is intended without the actuator)
- **Approvals** by CE, cULus

Applications

The safety magnetic sensors together with the magnetic actuator are particularly suitable to monitor protections of the safety gates that allow the entry to machines with dangerous movements, mainly in environment with strong presence of dust and dirtiness.
When connected to a safety module, the system can reach safety category up to category 4, PL e (EN ISO 13849-1).

Main functions

- Actuation without mechanical contact for high durability in all environmental conditions.
- Sensors are completely sealed and so insensitive to dirt and dust.
- Compact dimensions together with all mechanical variant possibilities allow very high flexibility in the installation.
- Suitable for applications with large tolerances or where mechanical features may change over the time, thanks to the wide actuation range.

References

Order code

MC36CH □ □ □ □

Enter the code option instead of □

Code	Option	Description	Note
M	-	Magnetic	
C	-	Rectangular size	
36	-	36mm length	
C	-	Plastic	
H	-	Reed contact	
□	2O	Contacts: 2 normally open	With open guard
	1O1C	Contacts: 1 normally open and 1 normally closed	With open guard
	2O1C	Contacts: 2 normally open and 1 normally closed	With open guard
□	L	Left exit	
	R	Right exit	
□	A2	Connection type: PVC cable 2m	
	M5	Connection type: M8 integrated connector	
	T1	Connection type: pig tail with M12 connector	
□	Null	No LED	
	L	With LED indicator	

Magnetic actuator

MC36CM

Type selection

Left exit



Connection	Output type	LED	Ordering no.
PVC cable 2m	2NO	No	**MC36CH2OLA2**
		Yes	**MC36CH2OLA2L**
	1NO + 1NC	No	**MC36CH1O1CLA2**
		Yes	**MC36CH1O1CLA2L**
	2NO + 1NC	No	**MC36CH2O1CLA2***
		Yes	**MC36CH2O1CLA2L***
M8 integrated connector	2NO	No	**MC36CH2OLM5**
		Yes	**MC36CH2OLM5L**
	1NO + 1NC	No	**MC36CH1O1CLM5**
		Yes	**MC36CH1O1CLM5L**
Pig tail with M12 connector	2NO	No	**MC36CH2OLT1***
		Yes	**MC36CH2OLT1L***
	1NO + 1NC	No	**MC36CH1O1CLT1***
		Yes	**MC36CH1O1CLT1L***


Right exit



Connection	Output type	LED	Ordering no.
PVC cable 2m	2NO	No	**MC36CH2ORA2**
		Yes	**MC36CH2ORA2L**
	1NO + 1NC	No	**MC36CH1O1CRA2**
		Yes	**MC36CH1O1CRA2L**
	2NO + 1NC	No	**MC36CH2O1CRA2***
		Yes	**MC36CH2O1CRA2L***
M8 integrated connector	2NO	No	**MC36CH2ORM5**
		Yes	**MC36CH2ORM5L**
	1NO + 1NC	No	**MC36CH1O1CRM5**
		Yes	**MC36CH1O1CRM5L**
Pig tail with M12 connector	2NO	No	**MC36CH2ORT1***
		Yes	**MC36CH2ORT1L***
	1NO + 1NC	No	**MC36CH1O1CRT1***
		Yes	**MC36CH1O1CRT1L***


* Available on request

Structure



Element	Component
A	Sensing face
B	Screw hole
C	M8, 4 pin, male connector


Dimensions [mm]



Sensing

Detection

Assured switching distance (S_{ao})	5mm with actuator MC36CM
Assured switch-off distance (S_{ar})	15mm with actuator MC36CM
Minimum distance between two sensors	50 mm



Note: the typical detection characteristic shown may vary from sensor to sensor.

Accuracy

Repeat accuracy (R)	≤ 10%

Features

Outputs

LED indication	Yellow (optional)
Type	2NO, 1NO+1NC, 2NO+1NC Reed contact
Rated operating voltage (U_e)	12-24 Vac/dc
Rated operating current (I_e)	0.25 A (resistive load)
Max switching load	6 W (resistive load)
Rated insulation voltage U_i (IEC EN 60947-1)	120 Vac (with cable / M12) 60 Vac / 75 Vdc (with M8 connector)
Rated impulse withstand voltage U_{imp} Line-to-ground (1.2/50 µs) Ri 500Ω	6 KV / 1.5 KV (with M8 connector)
Protection class	III
Reverse polarity protection	Yes

Response times

Max. operating frequency (f)	100 Hz
Response time	< 10 ms

Environmental

Operating temperature	-25° to +80°C (-13° to +176°F)
Storage temperature	-25° to +80°C (-13° to +176°F)
Vibration resistance EN 60068-2-6	10 g (10...150 Hz)
Shock resistance EN 60068-2-27	30 g (11 ms)
Degree of protection EN 60529	IP67; IP69K for M8 versions without LED
Pollution degree IEC 60947-5-1	3

Mechanical data

Housing material	PBT red
Weight	35 to 75g
Max torque for M8 version	1.5 Nm



- Use non-magnetic screw only.
- Fasten steadfastly the sensor and the actuator to the safety device (by means of rivets, tamper-proof screws, etc.).
- Fasten the sensor on plane surfaces only, in order to avoid possible distorsions that could damage the sensor or alter switching distances.
- To activate the safety sensors it is necessary to use the proper coded actuator MC36CM. Conventional magnets cannot be used.
- The sensor and actuator central reference marks must be opposed and aligned.

Electrical connection

Connection type	2m PVC cable 4 x 0.25 mm^2; 2m PVC cable 6 x 0.25 mm^2
	M8 4-pin connector
	Pig tail: PVC cable / 0.1 m; Ø 5 mm; with M12 connector

Compatibility and conformity

Conforms to the standards	EN/IEC 60947-5-1
Conforms to the directive	2006/42/CE Machinery Directive 2014/30/EU Electromagnetic Compatibility Directive 2011/65/UE RoHS Directive
Performance level (PL)	PL e - according to EN ISO 13849-1*
Safety category	Up to 4 - according to EN ISO 13849-1*
Terminal marking	In accordance with IEC 60947-5-1
B10d for each channel	700.000 operations (@ 250mA resistive load) Mechanical endurance: 80 millions operations
Approvals	

* When connected to a safety module

Connection Diagrams

Cable version




Fig. 1 *2 NO (without LED)*




Fig. 2 *2 NO (with LED)*




Fig. 3 *1 NO + 1 NC (without LED)*




Fig. 4 *1 NO + 1 NC (with LED)*




Fig. 5 *2 NO + 1 NC (without LED)*




Fig. 6 *2 NO + 1 NC (with LED)*

Colour code							
BN: Brown	WH: White	BK: Black	BU: Blue	GN: Green	GY: Grey	YE: Yellow	PK: Pink

M8 connector version




Fig. 7 *2 NO (without LED)*




Fig. 8 *2 NO (with LED)*




Fig. 9 *1 NO + 1 NC (without LED)*




Fig. 10 *1 NO + 1 NC (with LED)*

M12 connector version




Fig. 11 *2 NO (without LED)*




Fig. 12 *2 NO (with LED)*




Fig. 13 *1 NO + 1 NC (without LED)*




Fig. 14 *1 NO + 1 NC (with LED)*

COPYRIGHT ©2022
Content subject to change. Download the PDF: www.gavazziautomation.com