
Safety Magnetic Sensors
Cylindrical Safety Magnetic Sensors
Type SMSA3P02



- **Suitable for applications in safety category 4 in accordance with EN ISO13849-1:2015 when connected to appropriate safety devices**
- **1NO + 1NC outputs**
- **Cable output connection**
- **Cylindrical housing**
- **Multiple flux coding**
- **In compliance with CEI EN 60947-5-3:2000**

Product Description

The SMSA3P02 series is designed in conformity with EN ISO 12100:2010, EN 60204-1 and EN 1088. It is characterized by multiple flux coding and is suited for applications up to safety Category 4, in accordance with EN ISO13849-1:2015 when connected to appropriate safety devices.

Ordering Key

SMS A3 P 02

- **Safety magnetic sensor**
- **Diameter**
- **Housing material**
- **Contact type**

Type Selection

Output	Operating distance	Safety category	Item code
1 NO + 1 NC	15 mm	4	**SMSA3P02**

Output Specifications

Output	Category 4 (EN ISO13849-1:2015) 1 NO + 1 NC
Output Connection	Cable (PVC, AWG 26, L = 2 m 4 x 0,15 mm^2)
Contact ratings	
Max Switching Voltage	100 VAC
Max Switching Current	0.25 A
Max Switching Power	5 VA

General Specifications


Operating distance ON	15 ± 5 mm
Release distance OFF	20 ± 6 mm
Reset distance	25 ± 7 mm
Suitable magnetic unit	CLSA3
Misalignment	max ± 2 mm
Housing	
Dimensions	M30x1.5
Material	PBT + 30% glass
Weight	Approx. 70 g
Environment	
Degree of protection	IP 67
Operating temperature	-25 ÷ +70 °C
Storage temperature	-25 ÷ +70 °C
CE-marking	Yes

ООО «Сенсорен Электро» +7(495)150-48-00 info@sensoren.ru

Sensoren


CARLO GAVAZZI

Application




SMSA3P02 + NSC02


Operating Directions



Wiring Diagrams



Dimensions



ООО «Сенсорен Электро» +7(495)150-48-00 info@sensoren.ru
Sensoren