SPP 2605T 5

Diffuse Proximity

Photoelectric Sensors



Product Data	
Function	Both
Operation Mode	Diffuse Proximity
Supply Voltage	10 - 30 V dc
Control Feature	Sensitivity pot. and light/dark switch
Connection	5 m cable
Sensing Range	5 m
Output	NPN/PNP
Output Status	N.C./N.O.
Light Source	Infrared (880 nm)
Timer	On/Off Delay
Housing Material	Plastic
Housing	17 x 50 x 50

Technical Data	
Supply Voltage	10 – 30 V dc
Voltage Ripple	+/– 15 %
Reverse Polarity Protected	Yes
Short Circuit Protected	Yes
Current Consumption	< 65 mA
Max. Operation Frequency	72 Hz
Response Time ton / toff	7 ms / 7 ms
Output, Transistor	200 mA / 30 V dc
Power On Indicator	Green LED
Output Indicator	Yellow LED
Signal Status Indicator	Red LED
Hysteresis	5 – 15 %
Light Source	Infrared (880 nm)
Opening Angle	+/– 5°

COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.


Emission Angle	+/– 1,5°
Delay Time ton / toff	0 – 10 sec, adjustable
Housing Material, Front Lens	Polycarbonate
Housing Material, Sensor Housing	Polycarbonate / ABS
Cable	4 x 0,20 mm2
Cable Sleeve	PVC Ø 4,9 mm

Environmental Data	
Vibration	10 – 55 Hz, 0.5 mm
Shock	30 g
Operation Temperature	–20 to +55 °C
Storage Temperature	–40 to +80 °C
Sealing Class	IP 67
Light Immunity 15˚	25 000 lux


Approvals

CE UK CA

Wiring Diagram




*Do not connect black wire
Load as NPN



*Do not connect white wire
Load as PNP

COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Dimensions



COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.