# SMR 6202 TS J

## Thru Beam

Photoelectric Sensors




**Compatible Transmitter:**
SMT 6000 TS J

| Product Data | |
|---|---|
| Function | Receiver |
| Operation Mode | Thru Beam |
| Supply Voltage | 10 - 32 V dc |
| Connection | 4 pin, M12 plug |
| Sensing Range | 2 m |
| Output | PNP |
| Output Status | N.C. |
| Housing Material | Stainless Steel |
| Housing | M12 x 1 |


| Technical Data | |
|---|---|
| Supply Voltage | 10 - 32 V dc |
| Voltage Ripple | 15 % |
| Reverse Polarity Protected | Yes |
| Short Circuit Protected | Yes |
| Current Consumption | Max. 320 mW |
| Max. Output Load | 100 mA |
| Max. Residual Voltage | 2,5 V |
| Max. Operation Frequency | 1000 Hz |
| Response Time ton / toff | 0,5 ms / 0,5 ms |
| Output Indicator | Yellow LED |
| Hysteresis | Approx. 30 % |
| Opening Angle | +/- 6° |
| Housing Material, Front Lens | Polycarbonate |
| Housing Material, Sensor Housing | Stainless Steel (AISI 316 / 1.4401) |
| Cable | 3/4 x 0,14 mm² |
| Cable Sleeve | PVC Ø 4,0 mm |

COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

| Environmental Data | |
|---|---|
| Vibration | 10 - 55 Hz, 0.5 mm |
| Shock | 30 g |
| Operation Temperature | -20 to +60 °C |
| Storage Temperature | -40 to +80 °C |
| Sealing Class | IP 67 |
| Light Immunity 5˚ | > 50 000 lux |


## Approvals

## Wiring Diagram





## Connections

**4 pin, M12**





COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

## Parallel Displacement





**SMT 6000 and SMR 6x02**

## Angular Displacement




**SMR 6x02**

## Dimensions




COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.