FT 25-RA-60-NSU-M4M



Ordering information

Designation for ordering	FT 25-RA-60-NSU-M4M
Part number	**604-41001**
Order text	Working range 20...80 mm, red light, analogue 1...10 V, teach-in, NPN, N.O./N.C, metal connector M8x1, 4-pin For this product there is a new variant 604-41008 FT 25-RA-60-PNSUL-M4M This offers additional functions via IO-Link. Further product information can be found at www.sensopart.de
Components supplied	Operating manual, Sensor

Optical data	
Setting range *[mm]*	20 ... 80
Explanation of the setting range	Reference material 5...90% remission
Resolution *[mm]*	0.120
Explanation of resolution	12-bit
Linearity *[mm]*	0.40
Explanation of linearity	± 0.4 mm, reference material gray, 20% remission
Repeatability *[mm]*	≤ 0.40
Explanation of repeatability	Reference material gray, 20% remission, under constant ambient conditions
Hysteresis *[mm]*	2.5
Light source	LED
Light color	Red
Wavelength *[nm]*	632
Light spot size *[mm]*	See diagram
Switching frequency ≤ *[Hz]*	≤ 1,000
Explanation of switching frequency	ti/tp 1:1

Functions	
Display, LED yellow	Switching output indicator
Display, LED green	Operating voltage indicator
Setting options	Analogue measurement range QA Invertible analogue characteristic curve Switching output Q (switching window) N.O. / N.C. via teach-in button
Default settings	Analogue output QA (1...10 V): 20...80 mm Switching output Q, N.O. detection range: 20...80 mm
Measuring range adjustment	Via teach-in button

The information contained in this data sheet has been prepared with the utmost care. We reserve the right to make technical changes.

Electrical data

Operating voltage UB *[V DC]*	13 ... 30
No-load current *[mA]*	≤ 30
Output current *[mA]*	≤ 100
Readiness delay *[ms]*	≤ 300
Reverse polarity protection	Yes
Short circuit protection	Yes
Response time Q *[µs]*	≤ 500
Response time QA *[µs]*	≤ 400.0
Analog output QA	1 ... 10 V / max. 3 mA
Analog output QA voltage *[V]*	1 ... 10
Measured value output	Analog (voltage)
Protection class	2
Max. capacitive load *[nF]*	10
Output function	N.O./N.C.
Switching output Q	NPN
Number of outputs	1
Warm-up time *[Min.]*	10
Temperature profile *[mm/K]*	0.10


Mechanical data

Height *[mm]*	34.0
Length *[mm]*	20.0
Width *[mm]*	12.0
Weight *[g]*	~ 10
Front panel material	PMMA
Housing material	ABS
Ambient temperature: operation *[°C]*	-20 ... 60
Explanation of operation at ambient air temperature	UL: -20…+50 °C
Ambient temperature: storage *[°C]*	-20 ... 80
Protection class	IP 67, IP 69
Explanation of protection class	with IP 67 / IP 69 plug connected
Vibration and shock resistance	EN 60947-5-2
Connection name	Metal plug M8x1, 4-pin
- Number of pins	4
- Thread	M8x1
Housing type	Cuboidal

Technical drawings

The information contained in this data sheet has been prepared with the utmost care. We reserve the right to make technical changes.


Dimensional drawing



153-00839


Plug connection

Repeatability (typ.)




155-03761

Scanning properties




155-01666

Light spot size




155-01663

Connections




154-00543

Characteristic curves



Output and analog characteristic curve



Product link

https://www.sensopart.com/en/products/details/604-41001