
Proximity Sensors Capacitive, ATEX Thermoplastic Polyester Housing Type CB, Ø32, AC

TRIPLESHIELD™

CARLO GAVAZZI



- **Capacitive level sensor for solid, fluid or granulated substances**
- **Featuring *TRIPLESHIELD*™ sensor protection**
- **Rated operational voltage: 20-250 VAC**
- **Adjustable sensing distance 2-20 mm**
- **Output: SCR with or without fixed ON-delay of 30 sec.**
- **Make or break switching function**
- **LED indication**
- **High noise immunity**
- **Non-flush types**
- **Cable versions**
- **ATEX II 3DX T65°C**

Product Description

ATEX approved Capacitive proximity switches with sensing distance 20 mm non-flush mounted.
2-wire AC output with make (NO) and break (NC) switching. Grey Ø32 polyester housing with 2 m PVC cable.

Ideal for detecting grain or solids as level indicator in tanks, silos or containers.
Typical segments: agriculture, food & Beverage, conveyorbelts, plastic & rubber, etc.

Ordering Key

CB32CLN20TOFTAX

- **Capacitive proximity switch**
- **Housing style**
- **Housing size**
- **Housing material**
- **Housing length**
- **Detection principle**
- **Sensing distance**
- **Output type**
- **Output configuration**
- **Timer type**
- **ATEX**

Type Selection

Housing diameter	Rated operating dist. (S_n) [1]	Mounting	ON-delay	Ordering no. SCR/cable Make switching	Ordering no. SCR/cable Break switching	Ordering no. SCR/cable Make switching, ATEX	Ordering no. SCR/cable Break switching, ATEX
Ø32	20 mm	Non-flush	NO	CB32CLN20TO	CB32CLN20TC	CB32CLN20TOAX	CB32CLN20TCAX
Ø32	20 mm	Non-flush	YES	CB32CLN20TOFT	CB32CLN20TCFT	CB32CLN20TOFTAX	CB32CLN20TCFTAX

[1] Object: Grounded steel plate

Specifications

Rated operating dist. (S_n)	
CB32CLN20	2 to 20 mm factory set at 12 mm
Sensitivity Adj. multiturn	Pot. meter
Effective operation dist. (S_r)	$0.9 \times S_n \le S_r \le 1.1 \times S_n$
Usable operation dist. (S_u)	$0.8 \times S_r \le S_n \le 1.2 \times S_r$
Repeat accuracy (R)	≤ 5%
Hysteresis (H)	4 to 20% of sensing distance
Rated operational volt. (U_B)	20 to 250 VAC (ripple incl.)
Ripple	≤ 10%
Rated operational current (I_e)	
Continuous	$I_e \le 500$ mA
Short-time	< 2.5 A (max. 20 ms)
Min. load current	10 mA
Voltage drop (U_d)	≤ 10 VAC (at loads ≥ 20 mA)
Protection	Transients
Power ON delay	≤ 100 ms
Frequency of operating cycles (f)	10 Hz
Delay on operate (t_v)	30 sec
Indication for output ON	LED, yellow


Environment	
Degree of protection	IP 67 (Nema 1, 3, 4, 6, 13)
Temperature	
Operating temperature	-20° to +70°C (-4° to +158°F)
Operating temperature (AX)	-20° to +40°C (-4° to +104°F)
Storage temperature	-40° to +85°C (-40° to +185°F)
Housing material	
Body	PBT
Front	PBT
Connection	
Cable	Black, 2 m, 2 x 1.5 mm², Ø8 Oil proof PVC
Weight	
Cable version	270 g
Approvals	UL, CSA
AX versions only	ATEX zone 22 dust* ⟨Ex⟩ II 3 DX T65°C IP67
CE-marking	Yes

* • The cable must not be exposed to a pulling force.
• As the sensor surface exceed the allowed area the mounting fixture must be grounded.


ООО «Сенсорен Электро» +7(495)150-48-00 info@sensoren.ru

Sensoren

Dimensions




Wiring Diagrams



CB32CLN20TC(FT) CB32CLN20TO(FT)

Adjustment Guide

The environments in which capacitive sensors are installed can often be unstable regarding temperature, humidity, object distance and industrial (noise) interference. Because of this, Carlo Gavazzi offers as standard features in all *TRIPLESHIELD*™ capacitive sensors a user-friendly sensitivity adjustment instead of having a fixed sensing range, extended sensing range to accommodate mechanically demanding areas, temperature stability to ensure minimum need for adjusting sensitivity if temperature varies and high immunity to electromagnetic interference (EMI).



Installation Hints

Capacitive sensors have the unique ability to detect almost all materials, either in liquid or solid form. Capacitive sensors can detect metallic as well as non-metallic objects, however, their traditional use is for non-metallic materials such as:


- **Plastic Industry**
  Resins, regrinds or moulded products.
- **Agriculture**
  Feed, solids or grain.
- **Wood Industry**
  Saw dust, paper products, door and window frames.

Materials are detected due to their dielectric constant. The bigger the size of an object, the higher the density of material, the better or easier it is to detect the object. Nominal sensing distance for a capacitive sensor is referenced to a grounded metal plate (ST37). For additional information regarding dielectric ratings of materials please refer to Technical Information.


Delivery Contents

- Capacitive switch: CB32CL...
- Screw driver
- **Packaging:** Plastic bag
- Installation & Adjustment Guide

To avoid interference from inductive voltage/ current peaks, separate the prox. switch power cables from any other power cables, e.g. motor, contactor or solenoid cables




Relief of cable strain




The cable should not be pulled

Protection of the sensing face



A proximity switch should not serve as mechanical stop

Switch mounted on mobile carrier



Any repetitive flexing of the cable should be avoided

ООО «Сенсорен Электро» +7(495)150-48-00 info@sensoren.ru
Sensoren