



Inductive slot sensor

SC2-N0-GN

- 2 mm slot width

Dimensions



Technical Data


General specifications		
Switching function		Normally closed (NC)
Output type		NAMUR
Slot width		2 mm
Depth of immersion (lateral)		5 ... 7 mm , typ. 6 mm
Output type		2-wire
Nominal ratings		
Nominal voltage	U_o	8.2 V (R_i approx. 1 kΩ)
Operating voltage	U_B	5 ... 25 V
Switching frequency	f	0 ... 5000 Hz
Hysteresis	H	0.11 ... 0.2 mm
Current consumption		
Measuring plate not detected		≥ 3 mA

Release date: 2020-05-26 Date of issue: 2020-05-26 Filename: 095288_eng.pdf

Technical Data

Measuring plate detected	≤ 1 mA
Switching state indicator	LED, yellow
Functional safety related parameters	
$MTTF_d$	5790 a
Mission Time (T_M)	20 a
Diagnostic Coverage (DC)	0 %
Compliance with standards and directives	
Standard conformity	
NAMUR	EN 60947-5-6:2000 IEC 60947-5-6:1999
Electromagnetic compatibility	NE 21:2007
Standards	EN 60947-5-2:2007 EN 60947-5-2/A1:2012 IEC 60947-5-2:2007 IEC 60947-5-2 AMD 1:2012
Approvals and certificates	
IECEx approval	
Equipment protection level Ga	IECEx PTB 11.0091X
Equipment protection level Gb	IECEx PTB 11.0091X
Equipment protection level Da	IECEx PTB 11.0091X
Equipment protection level Mb	IECEx PTB 11.0091X
ATEX approval	
Equipment protection level Ga	PTB 99 ATEX 2219 X
Equipment protection level Gb	PTB 99 ATEX 2219 X
Equipment protection level Gc	PF13CERT2895 X
Equipment protection level Da	PTB 99 ATEX 2219 X
UL approval	cULus Listed, General Purpose
Ordinary Location	E87056
Hazardous Location	E501628
Control drawing	116-0453
CSA approval	cCSAus Listed, General Purpose
CCC approval	CCC approval / marking not required for products rated ≤36 V
Ambient conditions	
Ambient temperature	-25 ... 100 °C (-13 ... 212 °F)
Mechanical specifications	
Connection type	cable PVC , 500 mm
Core cross-section	0.06 mm^2
Housing material	PBT
Degree of protection	IP67
General information	
Use in the hazardous area	see instruction manuals

Connection



Release date: 2020-05-26 Date of issue: 2020-05-26 Filename: 095288_eng.pdf