PMV30A240

VOLTAGE MONITORING REALY FOR THREE-PHASE SYSTEM, WITHOUT NEUTRAL, MINIMUM AC VOLTAGE. PHASE LOSS AND INCORRECT PHASE SEQUENCE, 208...240VAC 50/60HZ



Product designation			Voltage monitoring relays
Product type designation			PMV30
General characteristics			
Description			Minimum AC voltage, phase loss and incorrect phase sequence relay
Type of system			Three-phase without neutral
Power supply			
Auxiliary supply voltage Us			Self powered
Operating voltage range			0.7...1.2 Ue
Rated frequency		Hz	50/60 ±5%
Power consumption Max		VA	11
Power dissipation Max		W	2.5
Control circut			
Rated voltage to control (Ue)			
	min	VAC	208
	Max	VAC	240
Voltage set-point (%Ue)			
	min	%	80…95
Tripping delay		s	0.1…20
Resetting time		s	0.1…20 (0.5 at power up)
Resetting hysteresis		%	3
Instantaneous tripping for Ue			Voltage <70% Ue
Type of reset			Automatic
Repeat accuracy		%	<±0.1
Tripping time for phase loss		ms	60
Relay outputs			
Number of relays		Nr.	1
Relay state			Normally energised De-energises at tripping
Contact arrangement			1 changeover SPDT
Rated operational voltage AC (IEC)		VAC	250
Maximum switching voltage		VAC	400
IEC Conventional free air thermal current Ith		A	8
UL/CSA and IEC/EN 60947-5-1 designation			B300
Electrical life (with rated load)		cycles	100000
Mechanical life		cycles	3000000
Functions			

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

PMV30A240


VOLTAGE MONITORING REALY FOR THREE-PHASE SYSTEM, WITHOUT NEUTRAL, MINIMUM AC VOLTAGE. PHASE LOSS AND INCORRECT PHASE SEQUENCE, 208...240VAC 50/60HZ

Modular version				2U
Minimum AC voltage				Yes
Maximum AC voltage				No
Phase loss				Yes
Incorrect phase sequence				Yes
Asymmetry				No
Indications				
Indication				1 green LED for power on and tripping and 1 red LED for tripping
Connections				
Terminals type				Screw
Tightening torque for terminals				
		max	Nm	0.8
		max	lbin	7
Conductor cross section				
	AWG/Kcmil			
		min	AWG	24
		Max	AWG	12
	IEC			
		min	mm²	0.2
		Max	mm²	4
Insulations				
Rated insulation voltage Ui			V	600
Rated impulse withstand voltage Uimp			kV	6
Operating frequency withstand voltage			kV	4
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-20
		max	°C	+60
	Storage temperature			
		min	°C	-30
		max	°C	+80
Housing				
Execution (n° of modules)				2
Material				Self-extinguishing polyamide
Mounting				35mm DIN rail (IEC/EN 60715)
IEC degree of protection				IP40 on front; IP20 at terminals
Dimensions (W x H x D)			mm	35.8 x 104.7 x 64.9
Weight			g	130
Dimensions				


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

PMV30A240

VOLTAGE MONITORING REALY FOR THREE-PHASE SYSTEM, WITHOUT NEUTRAL, MINIMUM AC VOLTAGE. PHASE LOSS AND INCORRECT PHASE SEQUENCE, 208...240VAC 50/60HZ



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 14
IEC/EN 60255-5
IEC/EN 61000-6-2
IEC/EN 61000-6-3
UL 508

Certificates

cULus
EAC

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

ETIM classification

ETIM 8.0	EC001438 - Voltage monitoring relay

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding