

MV7H 015-11Y

- **2 Contacts**
- **Metal enclosure**
- **3 Cable entry M 20 x 1.5**
- **Lever can be transposed by 180°**
- **67 mm x 75 mm x 43 mm (basic component)**
- **Continuous adjustment of lever position 360°**
- **Actuator head can be repositioned in steps 4 x 90°**

Data

Ordering data	
	MV7H 015-11Y
	101058467
EAN (European Article Number)	4030661032610
eCl@ss number, Version 9.0	27-27-06-01
Approval - Standards	
	CCC EAC
General data	
Product name	015 roller lever 7H
	EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Light-alloy diecast, paint finish
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	408 g
General data - Features	
Number of openers	1

Number of shutters	1
Mechanical data	
Actuating element	Roller lever
Mechanical life, minimum	10,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	2 x 1.2 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	3 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis
Actuating torque	0.2 Nm
Mechanical data - Connection technique	
Terminal Connector	Screw connection
	2.5 mm²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG
Mechanical data - Dimensions	
Height of sensor	228 mm
Length of sensor	43 mm
Width of sensor	67 mm
Width of Castor	9 mm
Diameter of Castor	36 mm
Ambient conditions	
Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C
Electrical data	
Thermal test current	10 A
Utilisation category AC-15	400 VAC
Utilisation category AC-15	2.5 A
Switching element	NO contact, NC contact
Note (Switching element)	galvanically separated contact bridges
Switching principle	Snap switch element
Bounce duration, maximum	2.5 ms
Switchover time, maximum	40 ms

Ordering code

Product type description:

(1)(2) 015-(3)Y-(4)

(1)

T Slow action (not available for AF/S)

M Snap action

(2)

S Plunger S

2S Telescopic plunger 2S

K Offset roller lever K

2K Tilt lever 2K

3K Angle roller lever 3K

8H Roller lever 8H

7H Roller lever 7H

10H Rod lever 10H

H Roller lever H

4H Spring rod lever on shaft 4H

2H Leaf spring lever 2H

3H Roller lever 3H

9H Rod lever 9H

6H Leaf spring lever 6H

(3)

11 1 NO contacts/1 NC contact

02 2 NC contact

20 2 NO contacts

(4)


UE Slow action with overlapping contacts

H Slow action with staggered contacts

C Magnetic blow-out

Pictures


Photo/Product/Catalogue



ID: kt15hfo4

| 359,6 kB | .jpg | 124.531 x 351.367 mm - 353 x 996 Pixel - 72 dpi
| 154,1 kB | .png | 74.083 x 208.844 mm - 210 x 592 Pixel - 72 dpi

Dimension/Product/Basic



ID: 1t015g02

| 8,3 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel - 72 dpi
| 158,3 kB | .jpg | 352.778 x 259.997 mm - 1000 x 737 Pixel - 72 dpi
| 32,1 kB | .cdr |


Diagramm/Product/Travel



ID: kt015s16

| 74,2 kB | .jpg | 352.778 x 244.475 mm - 1000 x 693 Pixel - 72 dpi
| 1,3 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel - 72 dpi


Graphic/Product/Contact



ID: k1o1sk07

| 37,9 kB | .jpg | 352.778 x 146.403 mm - 1000 x 415 Pixel - 72 dpi
| 17,3 kB | .cdr |


Dimension/Product/Actuator



ID: 1t15vb05

| 10,5 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel - 72 dpi
| 108,3 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701 Pixel - 72 dpi

Illistration/Product/Function



ID: 235hz02

| 16,8 kB | .cdr |
| 212,6 kB | .jpg | 352.778 x 870.656 mm - 1000 x 2468 Pixel - 72 dpi
| 3,8 kB | .png | 74.083 x 182.739 mm - 210 x 518 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on 512021-01-31T15:23:51+01:000301Europe/BerlinSun, 31 Jan 2021 15:23:51 +010051pmSunday.31pm31Europe/BerlinCET2301Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:23:51 +010001pm31