

GC-S84

Safety input / output unit

*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.

Specifications

Model		GC-S84
Input/output points	Safety inputs	8
	Safety outputs	4 (PNP)
	Safety relay output	-
	AUX outputs	
	Test outputs	2
Safety input specifications	Input device	Contact output device or PNP output device
	Input type	Type3
	ON level (voltage/current)	Min. 11 V/2 mA
	OFF level (voltage/current)	Max. 5 V/1.5 mA
	Short-circuit current	Approx. 3 mA
	Protection circuit	Surge protection circuit, wrong wiring protection circuit
	Maximum cable length	Max. 100 m 328.1'
Safety output specifications	Output type	PNP transistor output (DC-13, Type 0.5, Protected outputs)*1
	Maximum load current	500 mA
	Residual voltage (during ON)	Max. 2.0 V
	Leakage current (during OFF)	Max. 0.5 mA
	Maximum capacitive load	0.5 µF
	Load wiring resistance	Max. 2.5 Ω
	Protection circuit	Overcurrent protection circuit, reverse connection protection circuit
	Maximum cable length	Max. 30 m 98.4'
Safety relay output specifications	Output type	-
	Rated load (resistance load)	
	Rated load (inductive load)	
	Relay output mechanical life	
	Maximum cable length	
	B10d	
Test output specifications	Output type	PNP transistor output*2
	Maximum load current	100 mA*2
	Protection circuit	Overcurrent protection circuit, reverse connection protection circuit*2
	Maximum cable length	Max. 100 m 328.1'*3*2
AUX output specifications	Output type	-
	Maximum load current	
	Residual voltage (during ON)	
	Leakage current (during OFF)	

	Protection circuit	
	Maximum cable length	
Applicable standards	EMC	EMS: IEC 61131-2/-6, EN61131-2/-6,EMI: IEC 61131-2, FCC Part15B Class A, ICES-003, Class A
	Safety	IEC 61508, EN 61508 SIL3, IEC62061 SIL CL3, ISO/EN 13849-1:2015 Cat. 4, PL e, UL1998
Dimensions		22.2×95×90 mm 0.87"×3.74"×3.54" (W×D×H)
Power supply	Power voltage	24 VDC (-20 to +20%) Class 2
	Power consumption	Max. 60 mA
Environmental resistance	Ambient temperature	−10 to +55 °C 14 to 131 °F (No freezing)
	Relative humidity	5 to 85% (No condensation)
	Storage temperature	-25 to +70 °C -13 to 158 °F (No freezing)
	Operating altitude	Max. 2000 m 6561.7'
	Overvoltage category	II
	Pollution degree	2
	Vibration resistance	Frequency: 5 to 9 Hz, Half amplitude: 3.5 mm 0.14" Frequency: 9 to 150 Hz, Acceleration: 10 m/s² 10 times each in X, Y, Z directions
	Shock resistance	Acceleration: 150 m/s², Operating time: 11 ms, 3 times each in X, Y, Z directions
Material		Polycarbonate
Weight		Approx. 130 g

*1 Paragraph 6.4.6 Temporary overload of IEC 61131-2 supports up to 1.2 times the maximum load current.
*2 Test outputs do not comply with paragraph 6.4 of IEC 61131-2.
*3 When the test output is branched and connected to multiple safety input devices, the total branched cable length must not exceed 400 m 1312.3'.

Dimensions

* Download CAD file or product manual for larger image/text and more detail.

GC-S84





