SMR 3115 TP T3

Thru Beam

Photoelectric Sensors

Compatible Transmitter:
SMT 3000HC TP T3



Product Data	
Function	Receiver
Operation Mode	Thru Beam
Supply Voltage	10 - 30 V dc
Connection	3 pin, M8 plug
Sensing Range	15 m
Output	NPN
Output Status	N.O.
Housing Material	Plastic
Housing	M12 x 1


Technical Data	
Supply Voltage	10 - 30 V dc
Voltage Ripple	15 %
Reverse Polarity Protected	Yes
Short Circuit Protected	Yes
Current Consumption	Max. 8 mA
Max. Output Load	100 mA
Max. Residual Voltage	2,5 V
Max. Operation Frequency	> 40 Hz
Response Time ton / toff	< 13 ms / < 6 ms
Output Indicator	Yellow LED
Hysteresis	Approx. 30 %
Opening Angle	+/- 7°
Housing Material, Front Lens	Polycarbonate
Housing Material, Sensor Housing	Polycarbonate
Cable	3 x 0,14 mm²
Cable Sleeve	PVC Ø 3,4 mm

COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Environmental Data	
Vibration	10 - 55 Hz, 0,5 mm
Shock	30 g
Operation Temperature	-20 to +50 °C
Storage Temperature	-40 to +80 °C
Sealing Class	IP 67
Light Immunity 5˚	35 000 lux


Approvals

Wiring Diagram




Connections

3 pin, M8




COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Parallel Displacement




SMT 3000HC and SMR 3x15

Angular Displacement



SMR 3x15

Dimensions



COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.