ML 461-22Y



- **Metal enclosure**
- **2 cable entries M 20 x 1.5**
- **Lever can be transposed by 180°**
- **118 mm x 155 mm x 64 mm (basic component)**
- **Continuous adjustment of lever position 360°**
- **Actuator head can be repositioned in steps 4 x 90°**
- **In temperature-resistant version, the roller can be mounted in two different positions on the shaft**

Data

Ordering data	
	ML 461-22Y
	101059446
EAN (European Article Number)	4030661036045
eCl@ss number, Version 9.0	27-27-06-01
Approval - Standards	
	DNV.GL EAC
General data	
Product name	461 roller lever L
	EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Grey cast iron, galvanised
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	2,290 g

General data - Features	
Number of openers	2
Number of shutters	2
Safety appraisal - Safety outputs	
B10d Normally-closed contact (NC)	2,000,000 Operations
Mechanical data	
Actuating element	Roller lever
Mechanical life, minimum	5,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	max. 2 x 2.5 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	3 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis
Mechanical data - Connection technique	
Terminal Connector	Screw connection
	1.5 mm²
	2.5 mm²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG
Mechanical data - Dimensions	
Height of sensor	248 mm
Length of sensor	64 mm
Width of sensor	118 mm
Width of Castor	9 mm
Diameter of Castor	36 mm
Ambient conditions	
Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C
Ambient conditions - Insulation value	
Rated impulse withstand voltage	4 kV

Electrical data

Thermal test current	16 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Switching element	NO contact / NC contact
Note (Switching element)	with double break
Switching principle	Snap switch element
Bounce duration, maximum	5 ms
Switchover time, maximum	35 ms

Pictures

Photo/Product/Catalogue



ID: bt441f08

| 32,5 kB | .png | 74.083 x 70.203 mm - 210 x 199 Pixel - 72 dpi
| 119,1 kB | .jpg | 181.328 x 172.156 mm - 514 x 488 Pixel - 72 dpi


Photo/Product/Catalogue



ID: kt461f01

| 76,0 kB | .png | 73.731 x 122.061 mm - 209 x 346 Pixel - 72 dpi
| 1,1 MB | .jpg | 352.778 x 582.436 mm - 1000 x 1651 Pixel - 72 dpi

Dimension/Product/Basic



ID: 1t461g01

| 110,5 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691 Pixel - 72 dpi
| 9,2 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel - 72 dpi
| 35,2 kB | .cdr |

Diagramm/Product/Travel




ID: kt441s12

| 1,3 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel - 72 dpi
| 78,0 kB | .jpg | 352.778 x 260.703 mm - 1000 x 739 Pixel - 72 dpi

Illistration/Product/Function






ID: 235hz05

| 15,2 kB | .cdr |
| 180,5 kB | .jpg | 352.778 x 749.3 mm - 1000 x 2124 Pixel - 72 dpi
| 3,4 kB | .png | 74.083 x 157.339 mm - 210 x 446 Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1t422b07

| 113,5 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695 Pixel - 72 dpi
| 9,8 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on 492021-01-31T15:55:49+01:000301Europe/BerlinSun, 31 Jan 2021 15:55:49 +010049pmSunday.31pm31Europe/BerlinCET5501Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:55:49 +010001pm31