P2L81312

ROPE-PULL LEVER LIMIT SWITCH FOR NORMAL STOPPING, WITHOUT RESET BUTTON. CONTACTS 1NO+1NC. IP65. 120N OPERATING FORCE



Product designation				Rope-pull lever without reset button
Product type designation				P2L
General characteristics				
Material				
	Housing			Aluminium-zinc alloy
Contact characteristics				
Type of contact				1NO+1NC
Thermal current Ith			A	6
Rated insulation voltage Ui			V	400
Short-circuit protection with fuse			Class/A	10 gG/SC QUICK FUSE
IEC Conventional free air thermal current Ith			A	6
Resistance per pole (average value)			mΩ	<10
Mechanical features				
Operating head fixing				Fixed
Operating torque				
			N	120
			Ib	27
Tightening torque (Max)				
	Switch fixing			
			Nm	2.5
			lbin	22.1
Conductor section				
	AWG/Kcmil			
		max		14
	IEC			
		max	mm²	2.5
Cable connection				Self-releasing screw terminal
Cable entry				PG11 with cable gland
Weight			g	459
Operations				
Mechanical life			cycles	>10000000
Mechanical operation			cycles/h	3600
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			
		min	°C	-40
		max	°C	+70


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Resistance & Protection


IP degree

	Body housing	IP65
Pollution degree		3

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

EN 81-1.

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

	IEC/EN 60947-1
	IEC/EN 60947-5-1
Certificates	
	EAC
	IMQ

ETIM classification

ETIM 8.0	EC000030 - End switch

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding