SGT 14-085-016-A1-C-01-5

Self-Contained Light Curtains

Light Curtains



Compatible Receivers:

SGR 14-085-016-A1-C-08-5
SGR 14-085-016-A1-C-09-5

Product Data	
Function	Transmitter
Operation Mode	Thru Beam
Supply Voltage	12 - 36 V dc
Connection	5 m cable
Sensing Range	10 m
Number of Channels	16
Length	850 mm
Active Height	695 mm
Housing	12 x 30 mm

Technical Data	
Supply Voltage	12 – 36 V dc
Reverse Polarity Protected	Yes
Current Consumption	70 mA
Spacing between bottom & Ch1	25 mm
Channel Spacing	46 mm
Test Input	Yes
Power On Indicator	Green LED
Min. / Max. Sequencial Blanking Speed	1,6 m/s / 0,05 m/s
Light Source	Infrared (880 nm)
Profile Dimensions (w x d)	Slim Line (C), 12 x 30 mm
Housing Material, Front Lens	Polycarbonate
Housing Material, Profile	Aluminium (black anodised)
Cable	3 x 0,20 mm²
Cable Sleeve	PVC Ø 4,9 mm


COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Environmental Data	
Operation Temperature	–20 to +65 °C
Storage Temperature	–40 to +80 °C
Sealing Class	IP 67
Light Immunity 5˚	> 100 000 lux


Approvals

CE UK CA

Wiring Diagram




Parallel Displacement



Water-Resistant Slim Line C

COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Beam Patterns




46 mm channel spacing

COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Dimensions

Details



COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.