

T4VH355-20Z

- **Metal enclosure**
- **66,7 mm x 76 mm x 38 mm**
- **Mounting details to EN 50041**
- **Switching points to EN 50041**
- **3 cable entries lateral M 20 x 1.5**
- **Wide range of alternative actuators**
- **Good resistance to oil and petroleum spirit**
- **Actuator heads can be repositioned by 4 x 90°**

Data

Ordering data	
	T4VH 355-20Z
	101168383
EAN (European Article Number)	4030661222370
eCl@ss number, Version 9.0	27-27-06-01
Approval - Standards	
	cULus CCC EAC
General data	
Product name	T 355 roller lever H
Housing construction form	Norm construction design
	A
Enclosure material	Aluminium
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Lever material	Metal film
Roller material	Plastic
Gross weight	315 g

General data - Features	
Number of auxiliary contacts	2
Safety appraisal	
	BG-GS-ET-15 ISO 13849-1 EN 60947-5-1
Mission Time	20 Year(s)
Mechanical data	
Actuating element	Roller lever
Mechanical life, minimum	30,000,000 Operations
Actuating speed, maximum	2.5 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note (Switchover time)	Switchover time in accordance with actuating speed
Actuating torque, minimum	0.3 Nm
Mechanical data - Connection technique	
Terminal Connector	Screw connection
	0.75 mm²
	2.5 mm²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Mechanical data - Dimensions	
Height of sensor	129.5 mm
Length of sensor	60.6 mm
Width of sensor	66.7 mm
Ordering code	

Product type description:

(1)(2) 3(3)5-(4)Z(5)-(6)-(7)-(8)-(9)

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

H Roller lever H

10H Rod lever 10H

7H Roller lever 7H

1K Offset roller lever 1K

3K Angle roller lever 3K

RMS Brass roller

(3)

3 slim design

5 large design

(4)

11 1 NO contacts/1 NC contact

02 2 NC contact

20 2 NO contacts (not suitable for safety applications)

01/01 1 NC contact left / 1 NC contact right

12 1 NO contact/2 NC contacts

03 3 NC contact

(5)

H Slow action with staggered contacts

UE Slow action with overlapping contacts

(6)

G24 with LED

(7)

without	Cable entry M20
NPT	Cable entry NPT 1/2"
ST	M12 connector with A-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)
ST-2310	M12 connector with B-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)

(8)

2138 Roller lever 7H for position switches with safety function

(9)

1637 Gold-plated contacts

Pictures


Photo/Product/Catalogue



ID: k355hf01

| 469,8 kB | .jpg | 208.844 x 338.667 mm - 592 x 960 Pixel - 72 dpi
| 80,7 kB | .png | 74.083 x 119.944 mm - 210 x 340 Pixel - 72 dpi


Dimension/Product/Basic



ID: 1x355g01

| 10,6 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel - 72 dpi
| 132,5 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695 Pixel - 72 dpi
| 32,9 kB | .cdr |


Diagramm/Product/Travel



ID: kh335s04

| 53,5 kB | .jpg | 352.778 x 112.889 mm - 1000 x 320 Pixel - 72 dpi
| 1,7 kB | .png | 74.083 x 23.636 mm - 210 x 67 Pixel - 72 dpi
| 24,0 kB | .cdr |


Graphic/Product/Contact



ID: k--2sk01

| 51,9 kB | .jpg | 352.778 x 135.819 mm - 1000 x 385 Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1h336g01

| 84,5 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701 Pixel - 72 dpi
| 65,6 kB | .cdr |
| 4,1 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on 332021-01-31T05:11:33+01:000501Europe/BerlinSun, 31 Jan 2021 05:11:33 +010033amSunday.31am31Europe/BerlinCET1101Europe/BerlinJanuary2021Sun, 31 Jan 2021 05:11:33 +010001am31