# Product data sheet
## Characteristics

# XCSPL781
## safety switch XCSPL - elbowed flush lever - centred - 2NC -Pg11



### Main

| | |
|---|---|
| Range of product | Preventa Safety detection |
| Product or component type | Guard switch |
| Component name | XCSPL |
| Material | Plastic |
| Head type | Turret head rotary lever |
| Insulation | Double insulated |
| Type of operator | Elbowed flush lever |
| Operator direction information | Centred |
| Electrical connection | Terminal |
| Contacts type and composition | 1 NC + 1 NC |
| Contact operation | Slow-break |
| Clamping connection capacity | 1 x 0.5...2 x 1.5 mm² with or without cable end |
| Cable entry | 1 entry tapped for Pg 11 |
| Number of poles | 2 |

### Complementary

| | |
|---|---|
| Cable outer diameter | 7…10 mm |
| Positive opening | With NC contact |
| Tripping angle | 5 ° |
| Mechanical durability | 1000000 cycles |
| Minimum torque for tripping | 0.1 N.m |
| Positive opening minimum torque | 0.25 N.m |
| Contact code designation | A300, AC-15 (Ue = 120 V, Ie = 6 A) conforming to EN/IEC 60947-5-1<br>A300, AC-15 (Ue = 240 V, Ie = 3 A) conforming to EN/IEC 60947-5-1<br>Q300, DC-13 (Ue = 125 V, Ie = 0.55 A) conforming to EN/IEC 60947-5-1<br>Q300, DC-13 (Ue = 250 V, Ie = 0.27 A) conforming to EN/IEC 60947-5-1 |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 300 V conforming to UL 508<br>300 V conforming to CSA C22.2 No 14<br>500 V (pollution degree 3) conforming to EN/IEC 60947-1 |
| [Uimp] rated impulse withstand voltage | 6 kV EN/IEC 60947-5-1 |
| Maximum resistance across terminals | 30 mOhm conforming to EN/IEC 60947-5-4 |
| Short-circuit protection | 10 A cartridge fuse type gG (gl) |
| Safety level | Can reach category 4 with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach PL = e with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach SIL 3 with the appropriate monitoring system and correctly wired conforming to IEC 61508 |
| Safety reliability data | B10d = 5000000 value given for a life time of 20 years limited by mechanical or contact wear |
| Enclosure material | Polyamide PA66 fibre glass impregnated |
| Lever material | Stainless steel |
| Width | 30 mm |
| Height | 161 mm |
| Depth | 30 mm |
| Net weight | 0.095 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

| | |
|---|---|
| Standards | CSA C22.2 No 14<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-4<br>EN/ISO 12100<br>EN/IEC 60204-1<br>EN 1088/ISO 14119<br>UL 508 |
| Product certifications | CSA<br>BG<br>UL |
| Protective treatment | TC<br>TH |
| Ambient air temperature for operation | -25…70 °C |
| Ambient air temperature for storage | -40…70 °C |
| Vibration resistance | 50 gn (f= 10…500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 50 gn for 11 ms conforming to IEC 60068-2-27 |
| Electrical shock protection class | Class II conforming to EN/IEC 61140 |
| IP degree of protection | IP67 conforming to IEC 60529 |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 129 g |
| Package 1 Height | 3.2 cm |
| Package 1 width | 4 cm |
| Package 1 Length | 20.5 cm |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 20 |
| Package 2 Weight | 2.971 kg |
| Package 2 Height | 15 cm |
| Package 2 width | 30 cm |
| Package 2 Length | 40 cm |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |