# SGT 1-200-040-A1-C-00-3F

## Self-Contained Light Curtains

Light Curtains



**Compatible Receivers:**

SGR 1-200-040-A1-C-04-3F
SGR 1-200-040-A1-C-05-3F

| Product Data | |
|---|---|
| Function | Transmitter |
| Operation Mode | Thru Beam |
| Supply Voltage | 12 - 36 V dc |
| Connection | 3 m flexible cable |
| Sensing Range | 4 m |
| Number of Channels | 40 |
| Length | 2000 mm |
| Active Height | 1800 mm |
| Housing | 12 x 30 mm |


| Technical Data | |
|---|---|
| Supply Voltage | 12 – 36 V dc |
| Reverse Polarity Protected | Yes |
| Current Consumption | Max. 100 mA |
| Spacing between bottom & Ch1 | 25 mm |
| Distance, Beams Pinch Point | 23 mm |
| Channel Spacing | 46 mm |
| Test Input | Yes |
| Power On Indicator | Green LED |
| Time-out Function | Up to 4 non-adjacent channels, selectable |
| Light Source | Infrared (940 nm) |
| Profile Dimensions (w x d) | Slim Line (C), 12 x 30 mm |
| Housing Material, Front Lens | Polycarbonate |
| Housing Material, Profile | Aluminium (black anodised) |
| Cable | 3 x 0,14 mm² |
| Cable Sleeve | PVC Ø 4,1 mm |

COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.


| Environmental Data | |
|---|---|
| Operation Temperature | –20 to +65 °C |
| Storage Temperature | –40 to +80 °C |
| Sealing Class | IP 67 |
| Light Immunity 5˚ | > 100 000 lux |

## Approvals

## Wiring Diagram





## Parallel Displacement




**Slim Line A and Water-Resistant Slim Line C**

COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

## Beam Patterns





**46 mm channel spacing**

COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

## Dimensions

**Details**





COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.