M16 Sensor/Actuator connection
6-pin~8-pin,Field-Wireable Connector


M16,Straight Female




Characteristic

- 6-pin,7pin,8-pin
- Metal housing
- Cable feedthrough: Ø8 mm


6pins DIN standard
Modle:ZCK6-PG9
Order NO. 1651500




Female




7pins DIN standard
Modle:ZCK7-PG9
Order NO. 1651600




Female




7pins
Modle:ZCK7.1-PG9
Order NO. 1651700




Female



8pins DIN standard
Modle:ZCK8-PG9
Order NO. 1651800



Female



M16 Sensor/Actuator connection
6-pin~8-pin,Field-Wireable Connector


M16,Straight Male




Characteristic

- 6-pin,7pin,8-pin
- Metal housing
- Cable feedthrough: Ø8 mm


6pins DIN standard
Modle:ZCS6-PG9
Order NO. 1652500




Male




7pins DIN standard
Modle:ZCS7-PG9
Order NO. 1652600




Male




7pins
Modle:ZCS7.1-PG9
Order NO. 1652700




Male



8pins DIN standard
Modle:ZCS8-PG9
Order NO. 1652800



Male



M16 Sensor/Actuator connection
6-pin~8-pin,Field-Wireable Connector


M16,Angle Female




Characteristic

- 6-pin,7pin,8-pin
- Metal housing
- Cable feedthrough: Ø8 mm


6pins DIN standard
Modle:ZZCK6-PG9
Order NO. 1661500




Female




7pins DIN standard
Modle:ZZCK7-PG9
Order NO. 1661600




Female




7pins
Modle:ZZCK7.1-PG9
Order NO. 1661700




Female



8pins DIN standard
Modle:ZZCK8-PG9
Order NO. 1661800



Female



M16 Sensor/Actuator connection
6-pin~8-pin,Field-Wireable Connector


M16,Angle Male




Characteristic

- 6-pin,7pin,8-pin
- Metal housing
- Cable feedthrough: Ø8 mm


6pins DIN standard
Modle:ZZCS6-PG9
Order NO. 1662500




Male




7pins DIN standard
Modle:ZZCS7-PG9
Order NO. 1662600




Male




7pins
Modle:ZZCS7.1-PG9
Order NO. 1662700




Male



8pins DIN standard
Modle:ZZCS8-PG9
Order NO. 1662800



Male



M16 Sensor/Actuator connection
6-pin~8-pin,Field-Wireable Connector

Technical parameter

Housing	Copper-Zinc alloy
Housing surface	Nickel plated
Inserts (for contacts)	PBT
Contacts	Brass alloy
Contact surface at point of contact	Gold plated (0,25 µm)
Minimum mating cycles	> 1000
Type of protection	IP67, (screwed together)
Type of contacts	Solder
Temperature range	-40 °C – 125 °C
Cable diameter range	8 mm