31L48TPM240

TIME RELAY ON DELAY. MULTISCALE AND MULTIVOLTAGE, PLUG-IN AND FLUSH-MOUNT VERSION 48X48MM, 24VAC/DC, 110VAC, 220...240VAC



Product designation			Time relay
Product type designation			L48TP
General characteristics			
Description			On delay time relay, multiscale and multivoltage, plug-in version
Function			On delay
Supply circuit			
Rated auxiliary supply voltage Us			24VAC/DC; 110VAC; 220…240VAC
Rated frequency		Hz	50/60
Operating voltage range			0.85...1.1 Us
Maximum power consumption / dissipation		W	6VA
Immunity time for microbreakings		ms	≤40
Timing circuit			
Time setting range			18s...780min
Setting accuracy		%	±5
Repeat accuracy		%	±0.5
Influence of voltage variation		%	±0.5
Resetting time			
	During timing	ms	≥100
	Elapsed time	ms	≥65
Relay outputs			
Number of relays		Nr.	1
Contact arrangement			1 delayed C/O
Maximum switching voltage		VAC	250
IEC Conventional free air thermal current Ith		A	5
UL/CSA and IEC/EN 60947-5-1 designation			B300
Insulation (input-output)			
Rated insulation voltage Ui		V	250
Power frequency withstand voltage		kV	2
Operations			
Mechanical life		cycles	30000000
Electrical life (with rated load)		cycles	100000
Ambient conditions			
Temperature			
	Operating temperature		
	min	°C	-10
	max	°C	+60
	Storage temperature		
	min	°C	-30
	max	°C	+80
Housing			


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

31L48TPM240


TIME RELAY ON DELAY. MULTISCALE AND MULTIVOLTAGE, PLUG-IN AND FLUSH-MOUNT VERSION 48X48MM, 24VAC/DC, 110VAC, 220...240VAC

Material		Self-extinguishing polyamide
Mounting		Plug-in housing with 8-pin socket
Degree of protection		IP40 on front, IP20 terminals
Dimensions (W x H x D)	mm	48 x 48 x 90
Weight	g	124

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

- CSA C22.2 n°14
- IEC/EN 61812-1
- UL508

Certificates

- cURus
- EAC

ETIM classification

ETIM 8.0	EC001439 - Timer relay

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding