

MK 330-11Y

- **Long life**
- **Metal enclosure**
- **free of silicon**
- **1 Cable entry M 20 x 1.5**
- **Suitable for low actuating speeds**
- **proved in power station applications**
- **40 mm x 76 mm x 40 mm (basic component)**
- **Actuator heads can be repositioned by 4 x 90°**

Data

Ordering data	
	MK 330-11Y
	101163173
EAN (European Article Number)	4030661202525
eCl@ss number, Version 9.0	27-27-06-01
Approval - Standards	
	DNV.GL cULus CCC EAC
General data	
Product name	330 offset roller lever K
	EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Cast iron
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	190 g
General data - Features	
Number of openers	1

Number of shutters	1
Safety appraisal - Safety outputs	
B10d Normally-closed contact (NC)	20,000,000 Operations
Mechanical data	
Actuating element	Offset roller lever
Mechanical life, minimum	30,000,000 Operations
Actuating force, minimum	19 N
Contact opening	2 x 0.5 mm
Actuating speed, minimum	1 mm/min
Repeat accuracy of switching points	0
Mechanical data - Connection technique	
Terminal Connector	Screw connection
	1.5 mm²
	2.5 mm²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG
Mechanical data - Dimensions	
Height of sensor	113.5 mm
Length of sensor	40 mm
Width of sensor	40 mm
Width of Castor	8.5 mm
Diameter of Castor	18 mm
Ambient conditions	
Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C
	50 g / 6 ms
Ambient conditions - Insulation value	
Rated impulse withstand voltage	4 kV
Electrical data	
Thermal test current	6 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	2.5 A

Switching element	NO contact, NC contact
Note (Switching element)	galvanically separated contact bridges
Switching principle	Snap switch element
Bounce duration, maximum	43,221 ms
Switchover time, maximum	10 ms

Notes	
Note (General)	Actuation from the right should be avoided, since this reduces the mechanical life of the position switch.

Ordering code

Product type description:

M(1) 330-11Y-(2)-(3)

(1)

S Plunger S
2S Telescopic plunger 2S
R Roller plunger R
K Offset roller lever K
3K Angle roller lever 3K
3S Side plunger 3S
3R Side roller plunger 3R
AF Spring rod lever AF
4D Fork roller level 4D
8H Roller lever 8H
7H Roller lever 7H
10H Rod lever 10H
H Roller lever H
4H Spring rod lever on shaft 4H
2H Leaf spring lever 2H
3H Roller lever 3H
9H Rod lever 9H
6H Leaf spring lever 6H

(2)

without without LED switching conditions display
G24 with LED switching conditions display

(3)

AuNi Gold-nickel alloy contacts
1164 Splined shaft and lever available with 10° toothing

1366 For temperatures up to +160°C

Pictures


Photo/Product/Catalogue



ID: km330f11

| 150,4 kB | .png | 74.083 x 176.036 mm - 210 x 499 Pixel - 72 dpi
| 459,1 kB | .jpg | 142.169 x 338.314 mm - 403 x 959 Pixel - 72 dpi

Dimension/Product/Basic



ID: 1m330g01

| 107,3 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701 Pixel - 72 dpi
| 24,6 kB | .cdr |
| 4,0 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel - 72 dpi


Diagramm/Product/Travel



ID: km330s07

| 68,0 kB | .jpg | 352.778 x 206.375 mm - 1000 x 585 Pixel - 72 dpi
| 1,2 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel - 72 dpi

Graphic/Product/Contact



ID: k1o1sk07

| 37,9 kB | .jpg | 352.778 x 146.403 mm - 1000 x 415 Pixel - 72 dpi
| 17,3 kB | .cdr |

Illistration/Product/Function




ID: 235rz03



| 131,9 kB | .jpg | 352.778 x 773.642 mm - 1000 x 2193 Pixel - 72 dpi
| 15,5 kB | .cdr |
| 2,7 kB | .png | 74.083 x 162.278 mm - 210 x 460 Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1m330b11

| 86,6 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701 Pixel - 72 dpi
| 8,4 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on 072021-01-31T15:17:07+01:000301Europe/BerlinSun, 31 Jan 2021 15:17:07 +010007pmSunday.31pm31Europe/BerlinCET1701Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:17:07 +010001pm31