

CZ-H35S

Reflective Sensor Head with Shine Cancellation

CE

*Please note that accessories depicted in the image are for illustrative purposes only and may not be included with the product.


Specifications

Model		CZ-H35S
Type		Luster cancel
Detecting area		28 to 52 mm 1.10" to 2.05" (Reco mmended: 40 mm 1.57")
Smallest spot diameter		4.5 mm 0.18"dia. at reference distance of 40 mm 1.57"
Light source		Red LED (665 nm)/Green LED (520 nm)/Blue LED (465 nm)
Minimum bend radius of fi ber		25 mm 0.98"
Environmental resistance	Enclosure rating	IP40
	Ambient light	Incandescent lamp: 10,000 lux max., Sunlight: 20,000 lux max.
	Ambient temperature	-10 to +55 °C 14 to 131 °F (No freezing)
	Vibration resistance	10 to 55 Hz, Double amplitude 1.5 mm 0.06", 2 hours in each of the X, Y, and Z axis
Material		Housing：Triacetate, Polyarylate (Metal section: TYPE 304 stainless steel) , Lens cover：Fiberglass reinforced plastic
Weight		Approx. 40 g


Dimensions

* Download CAD file or product manual for larger image/text and more detail.


CZ-H35S




When a mounting bracket is attached



Mounting bracket
(Supplied with the CZ-H32, H35S, and H37S)



Material: TYPE 304 stainless steel
t=1.5
The figures in parentheses apply to CZ-H37S only.



Material: TYPE 304 stainless steel
t=1.2

Supplied screw: 20 x M3 screws (2)