
LCD touch process controllers | 2 standard signal inputs + analog and switching outputs | 573T



The process controller 573T with 2 analog inputs can be used in both single channel mode as well as in dual channel. In dual channel mode, all arithmetic operations are available for displaying the sum total, difference, ratio or the product. Inputs and outputs can be scaled separately.

Can be used as a simple process signal converter, process controller (ON/OFF controller) or for complex measuring tasks, where the relationship between two values, one to the other, must be monitored, calculated or further processed in a higher-level controller.

RoHS IO-Link Modbus



Innovative

- 2 separate freely scalable analog inputs ±10 V and 0/4 ... 20 mA, resolution 16 bit.
- Tare function – the unit can be set to 0 for any input voltage.
- Programmable linearization: with up to 24 control points, input via key-pad or via the teach-in function.
- Averaging measurement over 2 to 16 measuring cycles, for use with serious fluctuations of the input signals.
- Easy to program - the desired display value is simply keyed-in for a specific input signal.
- Fast 1 ms sampling rate per channel alternating.
- Serial interface RS232 or RS485 for reading data in and out.
- Total sum counter for single and total values – time-controlled or manually controlled.
- Optional IO-Link input/output interface with Device 1.1 protocol.

Compact and multifunctional

- Up to 3 display values in one device, display 1, display 2 + display calculated based on 1 and 2.
- AC and DC supply voltage in one device.
- Simple menu-driven programming via touch display, as well as tare or teach-in key.
- Can be used as a simple process signal converter, process controller (ON/OFF controller) or for complex measuring tasks where the relationship between two values, one to the other, must be monitored, calculated or further processed in a higher-level controller.
- Mathematical operation of the measured values of inputs 1 and 2. The result can also if required be multiplied, divided or added to an offset value, in order to obtain the desired display value.
- Analog output 0/4 ... 20 mA or ±10 V.
- 4 fast PNP switching outputs (reaction time < 1 ms), with switching hysteresis, step or tracking preset.
- Programmable display refresh time.

Multifunctional display

Large-scale 4-digit display over the whole display surface.

2-line display modes for the simultaneous display of 2 separate measured or calculated values.

Colour change of the display to green, yellow or red.



© Fritz Kübler GmbH, subject to errors and changes. 04/2026

LCD touch process controllers | 2 standard signal inputs + analog and switching outputs | 573T

Order code 6.573T . 01X . X0X . 001
(a) (b) (c) (d) (e)

(a) *Relay outputs*
0 = 2 relay outputs
2 = without output

(b) *Supply voltage*
3 = 18 ... 30 V DC
E = 18 ... 30 V DC + 115 ... 230 V AC


(c) *Further options*
0 = none

(d) *Electrical outputs*
0 = none
1 = RS232, 4 switching outputs
2 = RS232, 4 switching outputs, 16 Bit analog output
3 = RS485, 4 switching outputs
4 = RS485, 4 switching outputs, 16 Bit analog output

(e) *Option IO-Link*
(without IO-Link, omit the last 3 digits)
001 = IO-Link

Delivery specification
- Display 573T
- Gasket
- Mounting kit
- Manual German/English

Accessories / Mounting examples



		Type / size	Description		Order no.	
Mounting kit			1 kit consists of 2 latch hooks		6.0000.S050.0002	
Mounting frame		**cut-out 92 x 45 mm [3.62 x 1.77"]**	for snap-on mounting on 35 mm [1.38"] top-hat DIN rail	grey	**6.0000.F100.0001**	
Software for parameter setting OSxx			https://www.kuebler.com/de/docu-finder search box: OS1			

incl. in delivery

© Fritz Kübler GmbH, subject to errors and changes. 04/2026

LCD touch process controllers | 2 standard signal inputs + analog and switching outputs | 573T

Technical data

General technical data

Display	LCD touch display, 13 mm high 8 decades + sign, 3-color
Operating temperature	-20 °C ... +60 °C [-4°F ... +140°F] (non-condensing)
Storage temperature	-25 °C ... +70 °C [-13°F ... +158°F]
Altitude	up to 2000 m [6562’]

Electrical characteristics

Supply voltage		18 ... 30 V DC, with reverse polarity protection (rated voltage 24 V DC) 115 ... 230 V AC, 50/60 Hz (option)
Current consumption DC		100 mA, without load
Power consumption AC		approx. 3 VA, without load
Auxiliary power supply (for encoder)		
	AC supply	24 V DC ±15 %, 150 mA (up to +45 °C) 80 mA (from +46 °C)
	DC supply	U_B - 1 V, 250 mA
Reference output		
	output voltage	10 V DC
	accuracy	±0,1 %
	load	max. 10 mA / ≥ 1 kOhm
Device safety	designed to	EN 61010 part 1
	protection class	2
	application area	pollution level 2

Mechanical characteristics

Housing	ABS UL94–V-0
Weight	approx. 200 g
Protection	IP65 (front side) IP20 (rear side)
Terminals	max. 1.5 mm² / AWG16

Inputs

2 analog inputs		0 ... 20 mA, 4 ... 20 mA -10 ... +10 V
	input resistance current	Ri = 120 Ohm
	input resistance voltage	Ri = 50 kOhm
	measuring time per channel	min. 1 ms (programmable)
	resolution	16 bit (15 bit + sign)
	accuracy	±0.1 % ±1 digit
3 control inputs (Cnt 1 - 3)		PNP
	input frequency	max. 10 kHz
	input level	HTL: Low 0 ... 3 V / High 9 ... 30 V
	load	max. 2 mA / Ri > 15 kΩ / 470 pF

Outputs (option)

4 switching outputs		5 ... 30 V DC/200 mA (PNP)
	reaction time	< 1 ms
Interface		RS232 or RS485 Drivecom Protokoll / Modbus / Printer 9600 ... 38400 Baud
Analog output		-10 ... +10 V (max. 2 mA) or 0 ... 20 mA, 4 ... 20 mA (max. 270 Ω)
	resolution	16 bit (15 bit + sign)
	accuracy	±0.1 %
	reaction time	< 150 ms
Relay output		2 changeover contacts (potential free) max. 250 V AC / 3 A / 750 VA max. 150 V DC / 2 A / 50 W
	reaction time	< 20 ms

Interface characteristics IO-Link

Assembly / Revision	Device / 1.1
Bitrate	COM3
Port classe	Type A

Approvals


CE compliant in accordance with

EMC Directive	2014/30/EU
RoHS Directive	2011/65/EU
Low Voltage Directive	2014/35/EU


© Fritz Kübler GmbH, subject to errors and changes. 04/2026

LCD touch process controllers | 2 standard signal inputs + analog and switching outputs | 573T


Application examples



Monitoring of mixing ratios and display of flow rate



Level monitoring and adjustment, display of inflow and outflow




Material stretching, as well as monitoring of synchronous operation,
with display of individual speeds

© Fritz Kübler GmbH, subject to errors and changes. 04/2026


LCD touch process controllers | **2 standard signal inputs + analog and switching outputs** | **573T**

Connection example


Analog input, analog output, switching outputs



Analog input, switching outputs, interface RS232




Analog input, analog output, load output (relay), switching outputs



© Fritz Kübler GmbH, subject to errors and changes. 04/2026


LCD touch process controllers | 2 standard signal inputs + analog and switching outputs | 573T

Terminal assignment



Dimensions

Dimensions in mm [inch]



Panel cut-out
92 x 45 mm [3.62 x 1.77"]

© Fritz Kübler GmbH, subject to errors and changes. 04/2026