HS2B2NN025D024

HOCKEY PUCK TWO-PHASE, 25A, 3…32VDC, FASTON TERMINALS



Product designation			Solid state relay
Product type designation			HS2B
Type			Two-phase
Input characteristics			
Control voltage			3...32VDC
Operating voltage limits			
	Operating voltage pick-up	V	3
	Operating voltage drop-out	V	2
Input current at min…max voltage		mA	10...13
Input reverse voltage		V	32
Operating times			
Switching-on			Half cycle max
Switching-off			Half cycle max
Output characteristics			
Switching mode			Zero crossing
Rated operating voltage		VAC	12…280
Blocking voltage		V	600
Operational frequency (min…max)		Hz	45...65
Rated operating current AC-51 (resistive load) at 40°C		A	25
Rated operating current AC-51 (resistive load) at 55°C		A	21
Thermal resistance between junction to case		K/W	1.1
Heatsink for use at 40°C and 55°C at rated current AC-51		K/W	≤0.3
Operational current min		A	0.05
Non repetitive surge peak on state current t=10ms		A	250
Off state leakage current		mA	1
On state output voltage drop		V	1.6
Critical rate of rise of off-state voltage dv/dt		V/µs	500
Input - Output isolation		V	4000
Input - Output to metal base		V	2500
I2t		A2s	340
Terminal characteristics			
Control terminals		Type	Faston 4.8x0.8
Conductor section connectable (control terminals) with 1 or 2 wires min…max			
	AWG stranded	n°	16...14 (Faston lug)
	Flexible c/w insulated spade lug	mm2	0.75...6 (Faston lug)
Load terminals		Type	Faston 6.3x0.8
Conductor section connectable (load terminals) with 1 or 2 wires min…max			
	AWG stranded	n°	16...10 (Faston lug)
	Flexible c/w insulated spade lug	mm2	0.75...6 (Faston lug)
Operating position			
	allowable		Any

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding


Fixing			Screw

Ambient conditions


Temperature

Operating temperature			
	min	°C	-40
	max	°C	+90
Storage temperature			
	min	°C	-40
	max	°C	+100

Dimensions



Wiring diagrams



Certifications and compliance

Certifications

IEC/EN/BS 60335-1
IEC/EN/BS 60947-4-2
IEC/EN/BS 60947-4-3
IEC/EN/BS 62314

Compliance

CSA
cURus

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

VDE

ETIM classification

EC000066 - Power contactor, AC switching

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding