SGT 1-210-040-A1-B-00-3F

Self-Contained Light Curtains

Light Curtains



Product Data	
Function	Transmitter
Operation Mode	Thru Beam
Supply Voltage	12 - 36 V dc
Connection	3 m flexible cable
Sensing Range	4 m
Number of Channels	40
Length	2100 mm
Active Height	1800 mm
Housing	37,5 x 13 mm

Technical Data	
Supply Voltage	12 – 36 V dc
Reverse Polarity Protected	Yes
Current Consumption	Max. 100 mA
Spacing between bottom & Ch1	25 mm
Distance, Beams Pinch Point	23 mm
Channel Spacing	46 mm
Test Input	Yes
Power On Indicator	Green LED
Time-out Function	Up to 4 non-adjacent channels, selectable
Light Source	Infrared (940 nm)
Profile Dimensions (w x d)	Leading Edge (B), 37,5 x 13 mm
Housing Material, Front Lens	Polycarbonate
Housing Material, Profile	Aluminium (black anodised)
Cable	3 x 0,14 mm²
Cable Sleeve	PVC Ø 4,1 mm


COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Environmental Data	
Operation Temperature	–20 to +65 °C
Storage Temperature	–40 to +80 °C
Sealing Class	IP 54
Light Immunity 5˚	> 100 000 lux


Approvals

CE UK CA

Wiring Diagram




Parallel Displacement



Leading Edge B

COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Beam Patterns





46 mm channel spacing

COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Dimensions

Details





COPYRIGHT © TELCO SENSORS. ALL RIGHTS RESERVED. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.