

PSC1-C-10-MC

- **Memory card**
- **2 Signalling outputs**
- **2 safety relay contacts**
- **14 safe inputs on the base module**
- **Modular expansion with up to 64 inputs / outputs**
- **4 safe 2 A pp-switching semiconductor outputs, switchable to 2 safe p- / n-switching semiconductor outputs**

Data

Ordering data	
	PSC1-C-10-MC
	103008440
EAN (European Article Number)	4030661455020
eCl@ss number, Version 9.0	27-37-18-19
Approval - Standards	
	TÜV cULus EAC
General data	
Product name	PSC1
Terminal (mechanical)	Removable screw terminals
Gross weight	560 g
General data - Features	
SD Card Slot	Yes
Number of pulse outputs (test pulse output)	2
Number of relay outputs (1-channel)	2
Number of digital fail-safe inputs	14
Number of fail-safe digital outputs	4
Number of signalling outputs	2

Anzahl der Erweiterungsbaugruppen, maximal	2
Safety appraisal	
Performance level, up to	e
Control category to EN13849	4
PFH-value	1.26 x 10^{-8} /h
Safety Integrity Level (SIL), applicable for	3
Mission Time	20 Year(s)
Mechanical data	
Mounting	can be clipped into standard rail
Mechanical data - Connection technique	
	0.2 mm²
	2.5 mm²
Wire cross-section, minimum	24 AWG
Wire cross-section, maximum	12 AWG
Mechanical data - Dimensions	
Width	67.5 mm
Height	100 mm
Depth	115 mm
Ambient conditions	
	IP20
Ambient temperature, minimum	+0 °C
Ambient temperature, maximum	+50 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+70 °C
Relative humidity, minimum	5 %
Relative humidity, maximum	85 %
Note (Relative humidity)	non-condensing
Zulässige Aufstellhöhe über NN, maximum	2,000 m
Ambient conditions - Insulation value	
	III
	2
Electrical data	
Operating voltage, minimum	20.4 VDC
Operating voltage, maximum	28.8 VDC

Electrical data - Fail-safe digital outputs	
Rated operating current (safety outputs)	2,000 mA
Versions	short-circuit proof, p-type (Q2 und Q3)
Electrical data - Safe relay outputs	
Voltage, Utilisation category AC15	230 VAC
Current, Utilisation category AC-15	2 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	2 A
Electrical data - Electromagnetic compatibility (EMC)	
	DIN EN 62061 DIN EN 61800-3 DIN EN 61000-6-4 DIN EN 61000-6-7 DIN EN 61326-3 DIN EN 61000-6-2
Scope of delivery	
Included in delivery	Backplane bus connector Connector terminals

Pictures

Photo/Product/Catalogue



ID: kpsc1f09

| 73,8 kB | .png | 74.083 x 105.481 mm - 210 x 299 Pixel - 72 dpi
| 1,3 MB | .jpg | 352.778 x 502.356 mm - 1000 x 1424 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on 132021-01-31T12:49:13+01:001201Europe/BerlinSun, 31 Jan 2021 12:49:13 +010013pmSunday.31pm31Europe/BerlinCET4901Europe/BerlinJanuary2021Sun, 31 Jan 2021 12:49:13 +010001pm31