
KSL2V

PLASTIC MICRO SWITCH, K SERIES, METAL LEVER. 5MMM/2.13IN LONG FLAT LEVER. CONTACTS 1NO/NC. SCREW TERMINALSS




Product designation				Metal lever
Product type designation				KSL2
General characteristics				
Material				
		Housing		Polymer thermoplastic
Contact characteristics				
Type of contact				1NO/NC
Thermal current Ith			A	15
IEC/EN 60947-5-1 designation				A600 P300
Rated insulation voltage Ui			V	250
Switching speed				
		min	m/s	0.01
		max	m/s	1
Operating speed				
		min	m/s	0.05
		max	m/s	1
IEC Conventional free air thermal current Ith			A	15
Resistance per pole (average value)			mΩ	<15
Conductivity				10mA 5V
Mechanical features				
Terminals type				Screw
Operating head fixing				Fixed
Operating torque				
			N	1.3
			ozin	4.7
Weight			g	35
Operations				
Mechanical life			cycles	20000000
Electrical life			cycles	500000
Mechanical operation			cycles/h	240
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			
		min	°C	-40
		max	°C	+70
Resistance & Protection				
IP degree				
		Body housing		IP00 or IP20 with terminal shroud
Pollution degree				3
Dimensions				

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 14.
IEC/EN 60947-1
IEC/EN 60947-5-1
IEC/EN 61058-1
UL508

Certificates

cURus
EAC

ETIM classification

ETIM 8.0

EC000030 - End switch

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding