KPA1S11

PREWIRED WITH 2M LONG CABLE METAL LIMIT SWITCH, K SERIES, TOP PUSH ROD PLUNGER. CONTACTS 1NO+1NC SNAP ACTION




Product designation				Top push rod plunger
Product type designation				KPA1
General characteristics				
Material				
	Housing			Aluminium-zinc alloy
	Roller			Metal
Contact characteristics				
Type of contact				1NO+1NC Snap action
Thermal current Ith			A	10
IEC/EN 60947-5-1 designation				B300 R300
Rated insulation voltage Ui			V	400
Rated impulse withstand voltage Uimp			kV	4
Insulation class				I
IEC Conventional free air thermal current Ith			A	10
Resistance per pole (average value)			mΩ	<25
Conductivity				10mA 5V
Mechanical features				
Operating head fixing				Fixed
Operating torque				
			N	15
			Ib	3.4
Tightening torque (Max)				
	Switch fixing			
			Nm	2.5
			lbin	22.1
Cable connection				2m / 5xAWG18-0.75mm2 PVC Style 2517
Weight			g	286
Operations				
Mechanical life			cycles	>10000000
Mechanical operation			cycles/h	3600
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			
		min	°C	-40
		max	°C	+70
Resistance & Protection				
IP degree				
		Body housing		IP67


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Pollution degree	3

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

	CSA C22.2 n° 14.
	IEC/EN 60947-1
	IEC/EN 60947-5-1
	UL508

Certificates

	cULus
	EAC

ETIM classification

ETIM 8.0	EC000030 - End switch

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding