

EF10F.1

- **Flat plug-in connector**
- **11-12 (Contact labelling)**
- **Mounting flange position 1**

Data

Ordering data	
	EF10F.1
	101006560
EAN (European Article Number)	4030661463551
eCl@ss number, Version 9.0	27-37-13-02
Approval - Standards	
	cULus CCC EAC
General data	
Product name	Contact element EF
	EN 60947-5-1 IEC/EN 60947-1
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Contact labelling	11-12
Gross weight	20 g
General data - Features	
Number of openers	1
Mechanical data	
Installation instructions	pluggable

Mechanical life, minimum	10,000,000 Operations
positive break travel	2 mm
Contact opening	1 mm
Note Bounce duration	Bounce duration at an Actuating speed of 100mm/s
	1
Mechanical data - Connection technique	
Terminal Connector	Flat plug-in connector - 6.3 mm x 0.8 mm / 2 x 2.8 mm x 0.8 mm
Mechanical data - Dimensions	
Width	10 mm
Length	46 mm
Depth	60 mm
Ambient conditions	
	IP40
	IP20
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+80 °C
	110 g / 4 ms
Resistant to vibration	Resistance to vibration: 20 g / 10...200 Hz
Electrical data	
Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	8 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	5 A
	≥ 5 V / ≥ 3.2 mA
Switching element	Opener (NC)
Switching principle	Slow action
Bounce duration, maximum	5 ms
Switching frequency	1,200 /h

Pictures


Photo/Product/Catalogue



ID: kef10f01

| 41,8 kB | .png | 73.731 x 88.547 mm - 209 x 251 Pixel - 72 dpi
| 509,2 kB | .jpg | 352.425 x 422.981 mm - 999 x 1199 Pixel - 72 dpi


Diagramm/Product/Travel



ID: krf--s01

| 19,6 kB | .jpg | 352.778 x 80.433 mm - 1000 x 228 Pixel - 72 dpi
| 18,5 kB | .cdr |
| 1.020,0 b | .png | 74.083 x 16.933 mm - 210 x 48 Pixel - 72 dpi

Illistration/Product/Function



ID: krf--a06

| 17,0 kB | .cdr |
| 3,3 kB | .png | 74.083 x 164.042 mm - 210 x 465 Pixel - 72 dpi
| 133,2 kB | .jpg | 352.778 x 781.756 mm - 1000 x 2216 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on 032021-01-31T14:24:03+01:000201Europe/BerlinSun, 31 Jan 2021 14:24:03 +010003pmSunday.31pm31Europe/BerlinCET2401Europe/BerlinJanuary2021Sun, 31 Jan 2021 14:24:03 +010001pm31