TMM1NFC

MULTIFUNCTION TIME RELAY, MULTISCALE, MULTIVOLTAGE. 1 RELAY OUTPUT WITH NFC TECHNOLOGY AND APP. MODULAR VERSION, 12...240VAC/DC




Product designation				Time relay
Product type designation				TMM1NFC
Number of DIN modules				1
General characteristics				
Description				Multifunction time relay, programmable with NFC, multiscale and multivoltage
Function				Multifunction
Supply circuit				
Rated auxiliary supply voltage Us				12…240VAC/DC
Rated auxiliary supply voltage Us				
	AC			
		min	VAC	12
		Max	VAC	240
	DC			
		min	VDC	12
		Max	VDC	240
Rated frequency			Hz	50/60
Operating voltage range				0.85...1.1 Us
Maximum power consumption / dissipation			W	0.6VA/0.3W (12...48VAC/DC), 1.6VA/1.2W (110...240VAC/DC)
Immunity time for microbreakings			ms	≤25
Timing circuit				
Time setting range				0.1s…999days
Repeat accuracy			%	<±0.1
Influence of voltage variation			%	<±0.1
Influence of temperature variation			%	<±0.2
External command input				
		Minimum ON time	ms	25
		Connenction time		permanent
Resetting time				
		During timing	ms	≥100
		Elapsed time	ms	≥50
Relay outputs				
Number of relays			Nr.	1
Contact arrangement				1 delayed changeover
Maximum switching voltage			VAC	250
IEC Conventional free air thermal current Ith			A	8
UL/CSA and IEC/EN 60947-5-1 designation				B300
Insulation (input-output)				


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

Rated insulation voltage Ui			V	250
Rated impulse withstand voltage Uimp			kV	4
Power frequency withstand voltage			kV	2
Connections				
Terminals type				Screw
Tightening torque (Max)				
		Tightening torque Max	Nm	0.8
		Tightening torque Max	lbin	7 / 7...9 UL
Conductor section				
	AWG/Kcmil			
		min		24…12
		max		12…18
	IEC			
		min	mm²	0.2
		max	mm²	4
Operations				
Mechanical life			cycles	30000000
Electrical life (with rated load)			cycles	100000
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-20
		max	°C	+60
	Storage temperature			
		min	°C	-30
		max	°C	+80
Relative humidity			%	<90%
Maximum Pollution degree				2
Overvoltage category				III
Housing				
Execution (n° of modules)				1
Material				Self-extinguishing polyamide
Mounting				DIN rail 35 mm
Degree of protection				IP40 on front, IP20 terminals
Dimensions (W x H x D)			mm	17.5 x 104.7 x 64.9
Weight			g	86
Dimensions				

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding



Wiring diagrams



Certifications and compliance

Compliance

	CSA C22.2 n°14
	IEC/EN 61812-1
	UL508

Certificates

	CCC
	cULus
	EAC

ETIM classification

ETIM 8.0	EC001439 - Timer relay

The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding