M23 Adapter Connector ,Compatible with flange junction box and encoder


M23,Female




Characteristic

- 12-pin,17pin,19-pin
- Metal housing
- Clockwise/Anticlockwise arrangement
- Cable feedthrough: Ø10.5 mm

Clockwise
Modle:ZDK12-CW




Contact assignment




Dimension

Anticlockwise
Modle:ZDK12-AW




Contact assignment




Dimension

Clockwise
Modle:ZDK17-CW




Contact assignment




Dimension

Anticlockwise
Modle:ZDK17-AW




Contact assignment




Dimension

Anticlockwise
Modle:ZDK19-AW



Contact assignment



Dimension

M23 Adapter Connector ,Compatible with flange junction box and encoder


M23,Male




Characteristic

- 12-pin,17pin,19-pin
- Metal housing
- Clockwise/Anticlockwise arrangement
- Cable feedthrough: Ø10.5 mm

Clockwise
Modle:ZDS12-CW




Contact assignment




Dimension

Anticlockwise
Modle:ZDS12-AW




Contact assignment




Dimension

Clockwise
Modle:ZDS17-CW




Contact assignment




Dimension

Anticlockwise
Modle:ZDS17-AW




Contact assignment




Dimension

Anticlockwise
Modle:ZDS19-AW



Contact assignment



Dimension

M23 Adapter Connector ,Compatible with flange junction box and encoder

Technical parameter

Housing	Copper-Zinc alloy
Housing surface	Nickel plated
Inserts (for contacts)	PBT
Contacts	Brass alloy
Contact surface at point of contact	Gold plated (0,25 µm)
Minimum mating cycles	> 1000
Type of protection	IP67, (screwed together)
Type of contacts	Solder
Temperature range	-40 °C – 125 °C
Cable diameter range	10.5 mm