
CONTRINEX

INDUCTIVE SENSOR
EXTREME
DW-Ax-703-M30-1524

HOUSING	OPERATING DISTANCE	MOUNTING
M30	20 mm	Embeddable

- ✓ One-piece housing in stainless steel V2A
- ✓ Long operating distance
- ✓ Factor 1 on Fe and Al
- ✓ Anti-spatter coating
- ✓ IP68/IP69K





DW-AS-703-M30-1524

DETECTION DATA

Rated operating distance (S_n)	20 mm
Assured operating distance (S_a)	≤ (0.81 x S_n) mm
Repeat accuracy	≤ 0.7 mm
Hysteresis	3% S_r ≤ Hyst ≤ 15% S_r
Temperature drift	≤ 10% S_r
Standard target	60 x 60 x 1 mm³, FE360

Note: $0.9S_n \leq S_r \leq 1.1S_n$.

INTERFACE

Indicator LED, yellow	Sensing state ($0 \leq s \leq 0.8\ S_r$)
Indicator LED, yellow, blinking	Sensing state ($0.8\ S_r < s \leq S_r$)
IO-Link	✓
MTTF (@40°C)	1028 y

ELECTRICAL DATA

Supply voltage range (U_B)	10...30 VDC
Residual ripple	≤ 20% U_B
Output current	≤ 200 mA
Output voltage drop	≤ 2.0 VDC
Power consumption (no-load)	≤ 10 mA
Residual current	≤ 0.1 mA
Switching frequency	≤ 125 Hz
Short-circuit protection	✓
Voltage reversal protection	✓
Cable length max.	≤ 300 m

MECHANICAL DATA

Mounting	Embeddable
Housing material	V2A / 1.4305 / AISI 303 (+ coating)
Sensing face material	V2A / 1.4305 / AISI 303 (+ coating)
Max tightening torque	150 Nm
Ambient operating temperature	-25...+85°C[1]
Enclosure rating	IP68 / IP69K
Weight (cable/connector)	see page 2
Shock and vibration	IEC 60947-5-2

[1]Maximum temperature according to UL: 70°C.

Note: all data measured according to IEC 60947-5-2 standard with U_B=20 … 30VDC, T_A=23°C ± 5°C.

CONTRINEX AG Industrial Electronics
Route du Pâquis 3 – P.O. Box – CH 1720 Corminboeuf – Switzerland – **Tel:** +41 26 460 46 46
Fax: +41 26 460 46 40 – **Internet:** www.contrinex.com – **E-mail:** info@contrinex.com

CORRECTION FACTORS FOR TARGET OF


Steel FE 360	**1**	Copper	**0.9**	Aluminum	**1**	Brass	**1.3**	Stainless Steel V2A 1/2 mm	**0.4 / 0.75**

CORRECTION FACTORS FOR EMBEDDABLE MOUNTING IN SUPPORT OF

Steel FE 360	**0.85**	Aluminum	**0.7**	Brass	**0.6**	Stainless Steel V2A	**1.2**

Note: the operating distance of the sensor must be multiplied by the correction factor of the material. For example, the operating distance on Aluminum is $S_{n,\,Al} = S_n \times CF_{Al}$. In case of embeddable mounting, the distance is multiplied by the additional correction factor of the support, thus $S_{n,\,Al} = S_n \times CF_{Al} \times CF_{emb,\,Al}$.

INSTALLATION CONDITIONS



A : metal free zone
B : sensing face
C : support

a : 45 mm
b : 110 mm
c : 60 mm

d : steel 0 mm

Note: additional installation information can be found in the glossary of the Contrinex General Catalog.

IO-LINK FUNCTIONALITIES

IO-Link version	1.1
SIO mode	Supported
Process data	7-bit input
Baudrate	COM2 (38.4 kBaud)
Minimum cycle time	10.4 ms
ISDU	Not supported


IODD files may be downloaded from

www.contrinex.com/product-range/inductive-sensors/.


Select the product name to display the product page with corresponding downloads.

Alternatively, just click/scan the QR code on the left.

WIRING DIAGRAM



PIN ASSIGNMENT



M12

AVAILABLE TYPES

Part number	Part reference	Polarity	Connection	Output on pin 2	Output on pin 4 / bk	Weight
330-720-700	DW-AS-703-M30-1524	PNP	M12 4-pin	-	Normally open (NO) / IO-Link	137 g

Note: part reference may include additional suffix to indicate a revision version or special version. Further information is available on request.

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines. Terms of delivery and rights to change design reserved.

CONTRINEX AG Industrial Electronics

Route du Pâqui 3 – P.O. Box – CH 1720 Corminboeuf – Switzerland – **Tel:** +41 26 460 46 46
Fax: +41 26 460 46 40 – **Internet:** www.contrinex.com – **E-mail:** info@contrinex.com