

EFK103.1

- **Cage clamps**
- **Mounting flange position 1**
- **11-12; 23-24 (Contact labelling)**

Data

Ordering data	
	EFK103.1
	101167603
EAN (European Article Number)	4030661521329
eCl@ss number, Version 9.0	27-37-13-02
Approval - Standards	
	CCC EAC
General data	
Product name	Contact element EFK
	EN 60947-5-1 IEC/EN 60947-1
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Contact labelling	23-24
Gross weight	20 g
General data - Features	
Number of openers	1
Number of shutters	1
Mechanical data	
Installation instructions	pluggable

Mechanical life, minimum	10,000,000 Operations
positive break travel	2 mm
Contact opening	3 mm NO 1 mm NC
Note Bounce duration	Bounce duration at an Actuating speed of 100mm/s
	1
Mechanical data - Connection technique	
Terminal Connector	Cage clamps, WAGO-Cage-Clamp
	2 x 0.08 mm²
	2 x 1.5 mm²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Mechanical data - Dimensions	
Width	20 mm
Length	46 mm
Depth	51 mm
Ambient conditions	
	IP40
	IP20
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+80 °C
	110 g / 4 ms
Resistant to vibration	Resistance to vibration: 20 g / 10…200 Hz
Electrical data	
Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	8 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	5 A
	≥ 5 V / ≥ 3.2 mA
Switching element	NC contact, NO contact
Switching principle	Slow action
Bounce duration, maximum	5 ms
Switching frequency	1,200 /h

Pictures


Photo/Product/Catalogue



ID: kefkkf03

| 386,6 kB | .jpg | 352.425 x 352.778 mm - 999 x 1000 Pixel - 72 dpi
| 33,8 kB | .png | 74.083 x 74.083 mm - 210 x 210 Pixel - 72 dpi


Diagramm/Product/Travel



ID: krf--s06

| 30,6 kB | .jpg | 352.778 x 147.814 mm - 1000 x 419 Pixel - 72 dpi
| 19,0 kB | .cdr |
| 1,2 kB | .png | 74.083 x 31.044 mm - 210 x 88 Pixel - 72 dpi

Illistration/Product/Function



ID: krf--a07

| 4,3 kB | .png | 73.731 x 124.531 mm - 209 x 353 Pixel - 72 dpi
| 19,0 kB | .cdr |
| 184,6 kB | .jpg | 352.778 x 594.431 mm - 1000 x 1685 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on 102021-01-31T14:30:10+01:000201Europe/BerlinSun, 31 Jan 2021 14:30:10 +010010pmSunday.31pm31Europe/BerlinCET3001Europe/BerlinJanuary2021Sun, 31 Jan 2021 14:30:10 +010001pm31